

## Features and Benefits

### Commercial Tamper and Weather Resistant GFCI Receptacles

- Patented shutter design for tamper-resistant protection
- Meets NEC® requirements for TR (517-18c) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® self test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired


**GFTWRST83WIG**

**15A 125V**  
NEMA 5-15R  
UL CSA  
0.5 HP

**20A 125V**  
NEMA 5-20R  
UL CSA  
1 HP


### Hospital Grade • Tamper-Resistant and Weather Resistant GFCI Receptacles

Description	Rating	Color	Catalog Number	
Standard, Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black	<b>GFTWRST82BK</b>	<b>GFTWRST83BK</b>
		Brown	<b>GFTWRST82</b>	<b>GFTWRST83</b>
		Gray	<b>GFTWRST82GY</b>	<b>GFTWRST83GY</b>
		Ivory	<b>GFTWRST82I</b>	<b>GFTWRST83I</b>
		Light Almond	<b>GFTWRST82LA</b>	<b>GFTWRST83LA</b>
		Red	<b>GFTWRST82R</b>	<b>GFTWRST83R</b>
		White	<b>GFTWRST82W</b>	<b>GFTWRST83W</b>
Assembled in USA, Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black	<b>GFTWRST82BKU</b>	<b>GFTWRST83BKU</b>
		Brown	<b>GFTWRST82U</b>	<b>GFTWRST83U</b>
		Gray	<b>GFTWRST82GYU</b>	<b>GFTWRST83GYU</b>
		Ivory	<b>GFTWRST82IU</b>	<b>GFTWRST83IU</b>
		Light Almond	<b>GFTWRST82LAU</b>	<b>GFTWRST83LAU</b>
		Red	<b>GFTWRST82RU</b>	<b>GFTWRST83RU</b>
		White	<b>GFTWRST82WU</b>	<b>GFTWRST83WU</b>
Isolated Ground, Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black	<b>GFTWRST82BKIG</b>	<b>GFTWRST83BKIG</b>
		Brown	<b>GFTWRST82IG</b>	<b>GFTWRST83IG</b>
		Gray	<b>GFTWRST82GYIG</b>	<b>GFTWRST83GYIG</b>
		Ivory	<b>GFTWRST82IIG</b>	<b>GFTWRST83IIG</b>
		Light Almond	<b>GFTWRST82LAIG</b>	<b>GFTWRST83LAIG</b>
		Orange	<b>GFTWRST82ORIG</b>	<b>GFTWRST83ORIG</b>
		Red	<b>GFTWRST82RIG</b>	<b>GFTWRST83RIG</b>
White	<b>GFTWRST82WIG</b>	<b>GFTWRST83WIG</b>		
SNAPConnect®, Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black	<b>GFTWRST82SNAPBK</b>	<b>GFTWRST83SNAPBK</b>
		Brown	<b>GFTWRST82SNAP</b>	<b>GFTWRST83SNAP</b>
		Gray	<b>GFTWRST82SNAPGY</b>	<b>GFTWRST83SNAPGY</b>
		Ivory	<b>GFTWRST82SNAPI</b>	<b>GFTWRST83SNAPI</b>
		Light Almond	<b>GFTWRST82SNAPLA</b>	<b>GFTWRST83SNAPLA</b>
		Red	<b>GFTWRST82SNAPR</b>	<b>GFTWRST83SNAPR</b>
		White	<b>GFTWRST82SNAPW</b>	<b>GFTWRST83SNAPW</b>

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color thermoplastic wallplate, 20 amp feed-through capability.

See page Tech-10 for Tamper-Resistant and Weather Resistant descriptions.

### SNAPConnect® Right Angle Pigtailed Connector

Description	Wire Type	General Use	Assembled in USA
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; Polycarbonate housing material.	Solid	<b>SNAP1RA</b>	<b>SNAP1RNA</b>
	Stranded	<b>SNAP2RA</b>	<b>SNAP2RNA</b>
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; Polycarbonate housing material with WAGO terminals.	Solid	<b>SNAP1RAM2</b>	<b>SNAP1RNAM2</b>
	Stranded	<b>SNAP2RAM2</b>	<b>SNAP2RNAM2</b>

Note: For Assembled in USA products, must order connector with NA suffix.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).


**GFTWRST82AL**

**GFTWRST83GYU**

**GFTWRST82BKIG**

**GFTWRST83SNAPI**

**SNAP1RA**