



LED InstantFit Lamps

16.5PL-LED/24-3000 IF 10/1

Philips InstantFit LED Lamp, Long Compact (16.5W / 1900 lm / 3000K)

Philips LED T8 InstantFit Lamps are an ideal energy saving choice for existing linear fluorescent fixtures.

Product data

General Information	
Cap-Base	2G11 [2G11]
Main Application	Industrial
Nominal Lifetime (Nom)	40000 h
Switching Cycle	50000X
B50L70	40000 h
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	160 °
Initial lumen (Nom)	1900 lm
Luminous Flux (Rated) (Nom)	1900 lm
Rated Beam Angle	160 °
Correlated Color Temperature (Nom)	3000 K
Color Consistency	<6
Color Rendering Index (Nom)	82
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	16.5 W

Lamp Current (Nom)	120 mA
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	instant full light s
Power Factor (Nom)	0.9
Voltage (Nom)	120-277 V
Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	65 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Product Length	600 mm
Approval and Application	
Energy Saving Product	Yes

LED InstantFit Lamps

Suitable For Accent Lighting	No
Energy Efficiency Label (EEL)	A+
Approbation Marks	CE marking UL certificate RoHS compliance KEMA Keur certificate
Energy Consumption kWh/1000 h	21 kWh

Product Data


Order product name	16.5PL-LED/24-3000 IF 10/1
--------------------	----------------------------

EAN/UPC - Product	046677456634
Order code	456632
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001151304
Net Weight (Piece)	0.170 kg

Warnings and Safety

- Perform a visual inspection to ensure lamp holders (or sockets) are not damaged or loose. If the lamp holders (or sockets) are damaged, corroded, charred, blackened or loose, contact a qualified electrician for proper replacement.
- Please refer to the ballast compatibility guide located at www.philips.com/instantfit.


Dimensional drawing




LEDtube 500mm 16.5W/830

Product	D1	D2	A1	A2	A3
16.5PL-LED/24-3000 IF 10/1	33 mm	43.6 mm	564 mm	570.6 mm	570.6 mm

Photometric data



LEDtube 500mm 16.5 W 2G11



LEDtube 500mm 16.5W/830 2G11

LED InstantFit Lamps

