

## FEATURES & SPECIFICATIONS

### INTENDED USE

Provides task or accent lighting in commercial, retail, hospitality and residential applications. Ideal for use under and over cabinets, display cases, task lighting, office lighting, coves and utility/work areas.

### CONSTRUCTION

Low profile design, with on/off rocker switch. Can be direct wired or powered by 5' cord-and-plug (not included). Connect up to 354 watts of fixtures with 13" connector cord or 1-7/8" end row connector (Included). Rugged low profile aluminum housing, available in either white finish. Swivel head allows light to be directed to desired area.

### ELECTRICAL

Long-life LEDs, coupled with a high-efficiency driver, provide extended service life. Fixture is rated to deliver L70 performance at 50,000 hours and operates at 120 volts, 60Hz. Minimum starting temp -20F. Can direct-wire through rear access plate/knockout by utilizing the included Romex connector or by utilizing the optional UCD JB Junction/Splice box (sold separately).

Works with most standard incandescent dimmers (see list of approved dimmers).

### INSTALLATION

All mounting hardware included.

### LISTINGS

UL listed to US and Canadian safety standards. Title 24 qualified. Listed for damp locations.

### WARRANTY

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed.

Complete warranty terms located at: [www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**NOTE:** Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

Catalog Number
Notes
Type

Indoor General Purpose

# UCLD LED Linkable Cabinet Light

Linkable



SPECIFICATIONS	24"
<b>Lumens (3000K):</b>	740
<b>Watts (3000K):</b>	12.5
<b>Lumens per watt:</b>	59
<b>Length:</b>	24.12 (61.3)
<b>Width:</b>	3.63 (9.2)
<b>Height:</b>	1 (2.54)
<b>Weight:</b>	1.45 (.66)

All dimensions are inches (millimeters) unless otherwise indicated. Weights are pounds (kilograms).

### ORDERING INFORMATION


For shortest lead times, configure products using **bolded options**.

**Example:** UCLD 24IN 30K 90CRI SWR BZ

Series	Length	Color temperature	CRI	Options	Finish
<b>UCLD</b> Premium LED Undercabinet	24IN 2' Nominal	<b>30K</b> 3000K	<b>90CRI</b> >90	<b>SWR</b> On/off Rocker Switch	<b>BZ</b> Bronze

# UCLD LED Cabinet Light


Lithonia Lighting



<b>Light Output (Lumens)</b>	<b>740</b>
<b>Watts</b>	<b>12.56</b>
<b>Lumens per Watt (Efficacy)</b>	<b>58.92</b>

<b>Color Accuracy</b> <small>Color Rendering Index (CRI)</small>	<b>94</b>
---	-----------

**Light Color**  
Correlated Color Temperature (CCT)



**3000 (Bright White)**

2700K    3000K    4500K    6500K

All results are according to IESNA LM-79-2008: *Approved Method for the Electrical and Photometric Testing of Solid-State Lighting*. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the *Label Reference Guide*.

Registration Number: NJSM-QDWCI4 (2/24/2016)  
Model Number: UCLD 24IN 30K 90CRI  
Type: Luminaire - Directional

## COMPATIBLE DIMMERS

The UCLD is designed to operate with most standard Triac Based dimmers and is not compatible with 0-10v dimming systems. The following is a list of dimmers tested and does not imply any guarantee or warranty of compatibility with a particular application. Unlisted dimmers do not imply non-compatibility.

Manufacturer	Part number(s)
Lutron	DVELV-300P 300P SELV NTELV-300P
Pass & Seymour	HCL453PTCCCV6
SensorSwitch	nSP5 PCD 2W nSP5 PCDELV 120