

# Eaton C25FNF375AH

Catalog Number: C25FNF375AH

Eaton definite purpose contactor, Quick, 75A, 110-120 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 75A, Contactor, Three-pole, 90A, Box lugs (posidrive setscrew) and quick connect terminals , Non-reversing




Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton definite purpose contactor	C25FNF375AH
<b>UPC</b>	<b>Product Length/Depth</b>
782114117484	3.97 in
<b>Product Height</b>	<b>Product Width</b>
3.75 in	2.63 in
<b>Product Weight</b>	<b>Warranty</b>
2.8 lb	1 year
<b>Compliances</b>	<b>Certifications</b>
RoHS Compliant	UL Recognized CSA Certified

## Catalog Notes

Resistive Load rating per pole. Auxiliary contact includes quick connect terminals.

## defaultTaxonomyAttributeLabel

### Amperage Rating

75A

### Number Of Poles

Three-pole

### Type

Non-reversing

### Coil

24 Vac, 50/60 Hz

### Contact configuration

1 NO, 1 NC

### Enclosure

Open with metal mounting plate

### Frame size

15-50 A, two-pole and three-pole

### Inductive full load

75 A

### Model

Contactors

### Resistive load

90 A

### Terminals

Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)

### Connection

Quick

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Specifications and datasheets

[Eaton Specification Sheet - C25FNF375AH](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)