

Product Number: 74377

Order Abbreviation: VAPOR1B/040UNVD850/48EC/GR

General Description: Vapor Tight 1B, 40 Watts, 120-277V, 0-10V Dimmable, 80+ CRI, 5000K, canopy distribution, gray finish



Product Information

Power Factor	?0.90
Primary Lamp Type	SMD
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Total Harmonic Distortion (THD)	?20 %
Efficacy (LPW)	137
Abbrev. With Packaging Info.	VAPOR1B040UNVD85048ECGR 4/CS 1/SKU
Color Temperature/CCT (K)	5000
Ordering Abbreviation	VAPOR1B/040UNVD850/48EC/GR
Average Rated Life 1 (hr)	120000
Lumens	5300
Nominal Voltage (V)	120.00
Nominal Wattage (W)	40.00
UPC Code	UPC046135743771
Color Rendering Index (CRI)	>80
Service Life Rating	?120000
Lumens (lm)	5300
Wattage (W)	40.00
Accessories	Chain mount bracket
Color Range	5000 K
Connectors	Quick Disconnect
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Polycarbonate (PC)
Luminaire Finish	Gray
Luminaire Type	Vapor-tight
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Power Input	40
Mounting	Surface, Pendant, Suspended
Dimensions	48.5x4x3.3
Certification Listing	cULus, FCC, RoHS, DLC