



Product Number: 74488

Order Abbreviation: WALPAK2N/050UNV750/NC/BZ/P

General Description: Walpack Non-cutoff 2N, 50 Watts, 120-277V, 70+ CRI, 5000K, non-cutoff distribution, bronze finish, photocontrol

Product Information

Power Factor	?0.90
Primary Lamp Type	COB
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Total Harmonic Distortion (THD)	?20 %
Efficacy (LPW)	116
Abbrev. With Packaging Info.	WALPAK2N050UNV750NCBZP 1/CS 1/SKU
Color Temperature/CCT (K)	5000
Ordering Abbreviation	WALPAK2N/050UNV750/NC/BZ/P
Average Rated Life 1 (hr)	150000
Lumens	5600
Nominal Voltage (V)	120.00
Nominal Wattage (W)	50.00
UPC Code	UPC046135744884
Color Rendering Index (CRI)	>70
Service Life Rating	?150000
Lumens (lm)	5600
Wattage (W)	50.00
Color Range	5000 K
Connectors	Flying leads
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Bronze
Luminaire Type	Wall pack
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Mounting	Surface
Dimensions	14.4x7.1x9.3
Certification Listing	cULus, FCC, RoHS, DLC