



Product Number: 74914

Order Abbreviation: WALPAK2C/075UNV740/CO/BZ

General Description: Wallpack2C, 75 watts, 120-277V, 70+ CRI, 4000K, cutoff distribution, bronze finish

Product Information

Power Factor	?0.90
Primary Lamp Type	COB
Total Harmonic Distortion (THD)	?20 %
Efficacy (LPW)	120
Abbrev. With Packaging Info.	WALPAK2C075UNV740COBZ 1/CS 1/SKU
Color Temperature/CCT (K)	4000
Ordering Abbreviation	WALPAK2C/075UNV740/CO/BZ
Average Rated Life 1 (hr)	150000
Lumens	9000
Nominal Voltage (V)	120.00
Nominal Wattage (W)	75.00
UPC Code	UPC046135749148
Color Rendering Index (CRI)	>70
Service Life Rating	?150000
Lumens (lm)	9000
Wattage (W)	75.00
Color Range	4000 K
Connectors	Flying leads
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Bronze
Luminaire Type	Wall pack
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Power Input	75
Mounting	Surface
Dimensions	14.3x5.7x9.3
Certification Listing	cULus, FCC, RoHS, DLC