

Photocontrol - NIGHTFOX Pro Select Grade Locking Type Electronic Photocontrol, 120-277 V, Black, 10kV/5kA Surge Protection Per C136.10

Item EK4536KL



PRODUCT DESCRIPTION

NIGHTFOX Pro Select grade long life photocontrols are designed to match the life of the LED lighting fixture. Our Select grade photocontrols are designed to last 15 years and are backed up by a 10 year warranty.

FEATURES

- ▶ Non-drifting silicon light sensor, IR filtered for human eye response
- ▶ Exceeds 10,000 ON/OFF operations at full load, to meet life expectancy of LED fixtures
- ▶ Conformal coated PCB assembly
- ▶ All components meet 15-year life requirements
- ▶ For high-performance LED fixtures totaling 1650 W @ 277 VAC
- ▶ High precision, microprocessor-controlled zero-cross switching, individually calibrated to extend the life of 20 A relay independent of load being switched

TECHNICAL DATA

General

| | |
|--------------------------------|---|
| Model Number | EK4536KL |
| Description | NIGHTFOX Pro Select Grade Locking Type Electronic Photocontrol, 120-277 V, Black, 10kV/5kA Surge Protection Per C136.10 |
| UPC Code | 078275148994 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 10-Year limited |

Control Specifications

| | |
|------------------------------|--------------------------------|
| Sensor Time Delay | Instant ON; 2 sec to 5 sec OFF |
| Photocell Type | Silicon Diode |
| Photo Control Switch Type | Relay |
| Fail Mode | ON |
| Activation On | 1.5 fc |
| Activation Off | 2.25 fc |
| Photocontrol Type | Electronic |
| Application Compatibilities | LED; Incandescent; HID |
| Photocontrol Style | Locking type |
| Photocontrol Sensor Location | Side |

Dimensions

| | |
|-----------------------|-------|
| Product Height (mm) | 60.3 |
| Product Diameter (in) | 3.365 |
| Product Diameter (mm) | 85.5 |

Material Specifications

| | |
|------------------|-----------------------------------|
| Cover Color | Black |
| Housing Material | Polycarbonate with Acrylic Window |

Load Ratings

| | |
|--|----------------------------|
| Magnetic Ballast Range(s) | 1800 VA |
| Tungsten Range(s) | 1000 W |
| Electronic Ballast Load Ratings Ranges | 6 A, 120-277 VAC, 50/60 Hz |

Electrical Specifications

| | |
|-----------------------------|-----------------------|
| Input Voltage Range(s) | 120-277 VAC, 50/60 Hz |
| Surge Protection Technology | 510 J MOV |

Packaging

| | |
|---------------------------------------|-------------------------|
| Shipping Weight (lbs) | 0.25 |
| Unit Carton Dimensions (H x W x D) in | 2.75 x 3.375 x 3.375 in |

Operating Specifications

| | |
|--------------------------------|-------|
| Expected Lifetime (Years) | 15 |
| Expected Lifetime (Operations) | 10000 |

Environmental Specifications

| | |
|-------------------------|-------------|
| Temperature (operation) | -40°C..70°C |
| Usage Environments | Outdoor |

Standards and Certifications

| | |
|--|--------------|
| UL Certification | cULus |
| Other Certifications and Compatibilities | Ansi C136.10 |
| California Proposition 65 | None |
| RoHS Certification | Y |

ACCESSORIES



K121
Locking Type Receptacle, 3-Pin, C136.10
Compliant, 9" lead



K121-30
Locking Type Receptacle, 3-Pin, C136.10
Compliant, 30" lead



K122
Locking Type Receptacle, 3-Pin, C136.10
Compliant, with Pole Mounting Bracket



K171H
Locking Type Receptacle, 7-Pin, C136.41
Compliant, 12" lead



KPT0170-010
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Always-On, 10' cable



KPT1170-010
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Dusk-to-Dawn, 10' cable



SK4500K
Shorting Plug for Locking Type Receptacles



KPT0170-015
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Always-On, 15' cable



SK4500KMX
Shorting Plug for Locking Type Receptacles