HellermannTyton

596-00664

WARNING Turo Of PV Power	Article Number: 596-00664
Secure (Jebel Rar Sak anomen Sak Sak Sak Sak Sak Sak Sak Sak Sak Sak	Solar Label, Warning - Turn Off PV Label, 4.12" X 2.0", Vinyl, Orange/White, 10/pkg
14012/101 - 04440/0444/04/100	Rohs
WARNING	
TURN OFF PHOTOVOLTAIC AC DISCONNECT PRIOR TO WORKING INSIDE PANEL	
-	
Download spec sheet	

Base Data

Local Order Number	596-00664
Туре	WTOPVLBL10
Color	Red (RD)
Features and Benefits	 Made with UV stable inks and materials for durability and weather resistance. The labels are supplied with aggressive adhesive to ensure long life. Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	4.12" X 2" Black text on an Orange/White background that reads as: "WARNING - TURN OFF PHOTOVOLTAIC AC DISCONNECT PRIOR TO WORKING INSIDE PANEL." - 10 per pkg.
Short Description	Solar Label, Warning - Turn Off PV Label, 4.12" X 2.0", Vinyl, Orange/White, 10/pkg

Product Dimensions

Width W (Imperial)	4.12 "
Width W (Metric)	104.6 mm
Height H (Imperial)	2.0 "
Height H (Metric)	50.8 mm

Logistics and Packaging

Quantity Per	pack
Package Quantity	10
Package Quantity (Metric)	10

Material and Specifications

Material	Vinyl
Material Shortcut	VL
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Halogenfree	Yes
Operating Temperature	-40°F to +174°F (-40°C to +79°C)

ROHS Compliant Yes

UL Recognized (US) Yes

© HellermannTyton 2015