


596-00851

Article Number: 596-00851

Printable Solar Label, DC RATING LABEL, 3.75" X 2.00", Polyester, Red, 10/Pkg



Download spec sheet

Base Data

Local Order Number 596-00851

Type DCRATING10

Color Red (RD)

Features and Benefits

- Made with UV stable inks and materials for durability and weather resistance.
- The labels are supplied with aggressive adhesive to ensure long life.
- Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 3.75" X 2" White text on red background that reads as: "PV SYSTEM DC DISCONNECT; OPERATING CURRENT; OPERATING VOLTAGE; MAXIMUM SYSTEM VOLTAGE; SHORT CIRCUIT CURRENT." 10 per pack. 50 per roll. Label is also printable using a thermal transfer printer to add the variable voltage information on demand.

Short Description Printable Solar Label, DC RATING LABEL, 3.75" X 2.00", Polyester, Red, 10/Pkg

Product Dimensions

Width W (Imperial) 3.75 "

Width W (Metric) 92.25 mm

Height H (Imperial) 2.0 "

Height H (Metric) 50.8 mm

Logistics and Packaging

Quantity Per pack

Package Quantity 10

Package Quantity (Metric) 10

Material and Specifications

Material Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate

Material Shortcut 840/926

Adhesive Shortcut Acrylic

Adhesive Acrylic

Adhesive Operating Temperature -40°F to +180°F (-40°C to +82°C)

Halogenfree Yes

Operating Temperature -40°F to +302°F (-40°C to +150°C)

ROHS Compliant Yes

UL Recognized (US) Yes