



**Product Number:** 74528

**Order Abbreviation:** WALPAK3N/105UNV740/NC/BZ

**General Description:** Walpack Non-cutoff 3N, 105 Watts, 120-277V, 70+ CRI, 4000K, non-cutoff distribution, bronze finish

#### Product Information

Power Factor	?0.90
Primary Lamp Type	COB
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Total Harmonic Distortion (THD)	?20 %
Efficacy (LPW)	119
Abbrev. With Packaging Info.	WALPAK3N105UNV740NCBZ 1/CS 1/SKU
Color Temperature/CCT (K)	4000
Ordering Abbreviation	WALPAK3N/105UNV740/NC/BZ
Average Rated Life 1 (hr)	150000
Lumens	12500
Nominal Voltage (V)	120.00
Nominal Wattage (W)	105.00
UPC Code	UPC046135745287
Color Rendering Index (CRI)	>70
Service Life Rating	?150000
Lumens (lm)	12500
Wattage (W)	105.00
Accessories	Top visor, Wire guard
Color Range	4000 K
Connectors	Flying leads
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Bronze
Luminaire Type	Wall pack
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Power Input	105
Mounting	Surface
Dimensions	18x9.37x9.84
Certification Listing	cULus, FCC, RoHS, DLC