



Product Number: 74504

Order Abbreviation: GARAG1A/055UNVD750/G5/SV

General Description: Garage 1A, 55 watts, 120-277V, 0-10v dimmable, 5000K, Garage type V distribution, silver painted finish

Product Information

Power Factor	?0.90
Primary Lamp Type	SMD
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Total Harmonic Distortion (THD)	?20 %
Efficacy (LPW)	118
Abbrev. With Packaging Info.	GARAG1A055UNVD750G5SV 1/CS 1/SKU
Color Temperature/CCT (K)	4000
Ordering Abbreviation	GARAG1A/055UNVD750/G5/SV
Average Rated Life 1 (hr)	125000
Lumens	6200
Nominal Voltage (V)	120.00
Nominal Wattage (W)	55.00
UPC Code	UPC046135745041
Color Rendering Index (CRI)	>70
Service Life Rating	?125000
Lumens (lm)	6200
Wattage (W)	55.00
Color Range	4000 K
Connectors	Flying leads
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Silver
Luminaire Type	Garage
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Power Input	35
Mounting	Surface, Pendant
Dimensions	12.5x12.5x2.32
Certification Listing	cETLus, FCC, RoHS, DLC