



**Product Number:** 74911

**Order Abbreviation:** SLMFLD1A/050UNV850/WF/BZ

**General Description:** Slim Floodlight 1A, 50 watts, 120-277V, Dimmable, 80+CRI, 5000K, wide flood distribution, bronze painted finish

#### Product Information

Power Factor	?0.90
Primary Lamp Type	SMD
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Primary Lamp Type 1	SMD
Total Harmonic Distortion (THD)	?20 %
Efficacy (LPW)	121
Abbrev. With Packaging Info.	SLMFLD1A050UNV850WFBZ 1/CS 1/SKU
Color Temperature/CCT (K)	5000
Ordering Abbreviation	SLMFLD1A/050UNV850/WF/BZ
Average Rated Life 1 (hr)	150000
Lumens	5500
Nominal Voltage (V)	120.00
Nominal Wattage (W)	50.00
UPC Code	UPC046135749117
Color Rendering Index (CRI)	>80
Service Life Rating	?150000
Lumens (lm)	5500
Wattage (W)	50.00
Color Range	5000 K
Connectors	Wire nuts
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Bronze
Luminaire Type	Flood light
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Power Input	50
Dimensions	10.63x1.57x11.34
Certification Listing	cULus, FCC, RoHS, DLC