

Highbay Rounds

Series CPS-HBL-



Suitable Applications:

Commercial
Municipalities
Warehouse
Architectural

*120D as seen in photo above. See accessory page for 60D & 90D.

Wattage 100W | 150W | 200W | 240W

Color Temperature 4000K, 5000K, 6000K

Input Voltage AC 110 - 277 V / 480 V

CRI Ra>80

Ordering Information

Sample Part Number:

CPS-HBL-100W-UL-A-50

Series CPS-HBL-

Wattages / Lumens

100W 13000 L

200W 26000 L

150W 19500 L

240W 31200 L

Voltage

UH 480 V

UL 110-277 V

Lens

A Acrylic



Angle Degree

60D

90D

120D

Kelvin Temperatures

40 4000K

50 5000K

60 6000K

5 YEAR WARRANTY



IP 65 | IP 67



All part numbers below reflect 100 watts. Also available in 150, 200 and 240 watts in each version.*

*240 watts not available in UH.

CPS-HBL-100W-UH-120D-40	CPS-HBL-100W-UH-90D-40	CPS-HBL-100W-UL-120D-40	CPS-HBL-100W-UL-90D-40
CPS-HBL-100W-UH-120D-50	CPS-HBL-100W-UH-90D-50	CPS-HBL-100W-UL-120D-50	CPS-HBL-100W-UL-90D-50
CPS-HBL-100W-UH-120D-60	CPS-HBL-100W-UH-90D-60	CPS-HBL-100W-UL-120D-60	CPS-HBL-100W-UL-90D-60
CPS-HBL-100W-UH-60D-40	CPS-HBL-100W-UH-A-40	CPS-HBL-100W-UL-60D-40	CPS-HBL-100W-UL-A-40
CPS-HBL-100W-UH-60D-50	CPS-HBL-100W-UH-A-50	CPS-HBL-100W-UL-60D-50	CPS-HBL-100W-UL-A-50
CPS-HBL-100W-UH-60D-60	CPS-HBL-100W-UH-A-60	CPS-HBL-100W-UL-60D-60	CPS-HBL-100W-UL-A-60