

Lumen Smart Double Twins

Series CPS-LS-DTW-



Suitable Applications:

Commercial
Municipalities
Warehouse
Architectural

***Linkable up to 200W.**

Wattage	8W 15W 25W 30W 40W 44W 60W
Luminous Efficiency	120 Lumens / Watt
Length (in feet)	1, 2, 3, 4, 5, 6, 8
Color Temperature	4000K, 5000K
Input Voltage	AC 110 - 277 V
CRI	>70-80

Ordering Information

Sample Part Number:	CPS-LS-DTW-4-30W-UL-F-50	Series CPS-LS-DTW-
Wattages/ Lumens		Length (in feet)
8W 960 L	30W 3600 L 60W 7200 L	1 4 7
15W 1800 L	40W 4800 L	2 5 8
25W 3000 L	44W 5280 L	3 6 <i>DLC listed</i>
Voltage		Kelvin Temperatures
UL 110-277 V	Lens	40 4000K
	C Clear	50 5000K
	F Frosted	

All part numbers below reflect 8, 15, 25, and 30 watts. Also available in 40, 44, and 60 watts.

CPS-LS-DTW-1-8W-UL-C-40	CPS-LS-DTW-2-15W-UL-C-40	CPS-LS-DTW-3-25W-UL-C-40	CPS-LS-DTW-4-30W-UL-C-40
CPS-LS-DTW-1-8W-UL-C-50	CPS-LS-DTW-2-15W-UL-C-50	CPS-LS-DTW-3-25W-UL-C-50	CPS-LS-DTW-4-30W-UL-C-50
CPS-LS-DTW-1-8W-UL-F-40	CPS-LS-DTW-2-15W-UL-F-40	CPS-LS-DTW-3-25W-UL-F-40	CPS-LS-DTW-4-30W-UL-F-40
CPS-LS-DTW-1-8W-UL-F-50	CPS-LS-DTW-2-15W-UL-F-50	CPS-LS-DTW-3-25W-UL-F-50	CPS-LS-DTW-4-30W-UL-F-50

DOES NOT EMIT HARMFUL VAPORS OR GASES AND IS SHATTER RESISTANT

5 YEAR WARRANTY

