


PERIMETER WALL PACK NRG®300 SERIES	Cat.#		 HUBBELL Outdoor Lighting
	Job	Type	
			Approvals

INTENDED USES

- Entry or perimeter security lighting applications for commercial buildings, shopping centers, schools, and apartment complexes

CONSTRUCTION

- Full polycarbonate front provides vandal resistance and efficient spread. Lateral coverage on HID units is 5 times the typical mounting height up to 10 feet
- Internally painted bronze finish for lasting appearance
- LED unit is an excellent upgrade from HID systems featuring a 17w LED system with a 1700+ lumen output, 4000K or 5000K CCT, 80 CRI - 60,500 hr rated life at L94
- Rugged cast aluminum back housing for rigid mounting; Bottom 1/2" conduit knockout for surface conduit wiring (except on 'MS' unit). Back hub allows access to recessed wiring boxes; Two point mounting; Additional center-pin torx screws provided for tamper-resistant applications

ELECTRICAL

- HID versions with PC are 120V
- Lamp included with HID versions: Vertical medium base HID socket

LED

- Single driver 50/60 Hz, 120-277V
- NRG-356L is 1858/1794 lumens, 4000K/5000K, 112/110 IPW, CRI 80, 1 driver at 100mA
- PC version 120V-277V

LISTINGS

- Listed to UL 1598 for use in wet locations
- Some LED models meet DesignLights Consortium (DLC) qualifications, consult DLC website for more details: <http://www.designlights.org/QPL>

WARRANTY


For more information visit: <http://www.hubbellighting.com/resources/warranty/>

PRODUCT IMAGE(S)



NRG-356LU-5K-BZ

DIMENSIONS



SHIPPING INFORMATION

Catalog Number	G.W(kg)/CTN	Carton Dimensions			Carton Qty. per Master Pack
		Length Inch (cm)	Width Inch (cm)	Height Inch (cm)	
NRG356LU5KBZ	5.33 (2.42)	11.8 (30)	7.4 (19)	6.1 (15.5)	1
NRG356LU5KBZPC	5.40 (2.45)	11.8 (30)	7.4 (19)	6.1 (15.5)	1

CERTIFICATIONS/LISTINGS



ORDERING INFORMATION

Catalog Number ¹		Wattage	Voltage	Max Input Amps	Color	Weight lbs. (kg)
Without Photocontrol	With Photocontrol					
Pulse Start Metal Halide						
-	NRG-350B-PC^{1,2}	50w	120V	1.1	Bronze	6.5 (2.9)
56 LED – 1858/1794 lumens – 4000K/5000K – 80 CRI³						
NRG-356L-4K-U	NRG-356L-4K-U-PC	16.6w	120-277V	.15	Bronze	6 (2.7)
NRG-356L-5K-U	NRG-356L-5K-U-PC	16.3w	120-277V	.15	Bronze	6 (2.7)

1 Lamp included
2 120V NPF ballast for HID
3 LED units feature five year limited warranty

ACCESSORIES - ORDER SEPARATELY

Catalog Number	Description
PBT-1	Button photocontrol, 120V
PBT-234	Button photocontrol, 208, 240, 277V

REPLACEMENT PART - ORDER SEPARATELY

Catalog Number	Description
SM352-COVER	Polycarbonate front cover, Bronze



Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • Phone: 864-678-1000
Due to our continued efforts to improve our products, product specifications are subject to change without notice.

© 2017 HUBBELL OUTDOOR LIGHTING, All Rights Reserved • For more information visit our website: www.hubbelloutdoor.com • Printed in USA

NRG300X-SPEC 3/17