


WISE-TYPE CONNECTORS

- For main with tap
- One-piece, side loading.
- Cast copper.
- **Made in USA.** 





CATALOG NUMBER	CONDUCTOR RANGE TAP / MAIN	PCS. PER CTN.	WT. PER 100	NAED UPC NO. 632591-
VC-6SH*	#10 Sol. - #6 Sol.Cu	100	9	70750-3
VC-6SH-P*	#10 Sol. - #6 Sol.Cu	100	9	71506-5
VC - 4	#8 Sol. - #4 Sol.Cu	50	15	70751-0
VC - 2	#6 Sol. - #2 Sol.Cu	50	18	70752-7
VC-2S	#5 Sol. - #2 Sol.Cu	50	18	61355-2
VC-20	#4 Sol. - 1/0 Sol.Cu	50	25	61356-9
VC-20S	#3 Sol. - 2/0 Sol.Cu	20	36	61357-6
VC-40	#1 Sol. - 4/0 Sol.Cu	10	41	61358-3

*P = Plated

*SH = Slotted-Head Bolt

TYPE TTC TRANSFORMER TANK GROUND CONNECTORS

- High-conductivity bronze
- 1/2" - 13 stud fits all standard EEI-NEMA distribution transformers
- Accommodates cable in either horizontal or vertical direction
- P suffix indicates tin plated connector
- **Made in USA.** 
- **Veteran owned company.** 



CATALOG NUMBER	CONDUCTOR RANGE	STUD THREAD SIZE	DIMENSIONS			PCS. PER CTN.	WT. PER 100	NAED UPC NO. 632591-
			A-Length	Width	C-Height			
TTC-2	2/0 Str. to 8 Sol.	1/2--13	1-51/64	1-9/64	1-21/64	100	22	61366-8
TTC-3	1 Str. to 10 Sol.	1/2--13	1-3/8	1-3/64	1-9/16	100	20	61367-5
TTC-4	1 Str. to 10 Sol.	1/2--13	1-1/4	7/8	1-3/8	100	16	61368-2
TTC-2P	2/0 Str. to 8 Sol.	1/2--13	1-51/64	1-9/64	1-21/64	100	22	61369-9
TTC-3P	1 Str. to 10 Sol.	1/2--13	1-3/8	1-3/64	1-9/16	100	20	61370-5
TTC-4P	1 Str. to 10 Sol.	1/2--13	1-1/4	7/8	1-3/8	100	16	61371-2



TRANSFORMER GROUND CONNECTORS

- Made in USA. 



CATALOG NUMBER	CONDUCTOR RANGE	STUD THREAD SIZE	BOLT	PCS. PER CTN.	WT. PER 100	NAED UPC NO. 632591-
VC207	8 Sol. to 1/0 Str.	1/2 - 13 - UNC-2/4	9/16" Hex	25	10	61372-9

TYPE PAC ALUMINUM WITH COPPER LINER

- Corrosion resistant design and construction
 - No assembly required
 - Cast aluminum body surrounds copper liner, sealing out moisture
 - Made in USA. 
- Veteran owned company. 



CATALOG NUMBER STANDARD	CONDUCTOR RANGE			PCS. PER CTN.	WT. PER 100	NAED UPC NO.632591-
	Main	Tap				
	ACSR	Aluminum	Copper			
PAC 345	1/0 - 8	1/0 Sol. - 8 Str.	1/0 Sol. - 8 Str.	50	23	61380-4
PAC 7	336.4 - 1/0	400 - 2/0 1/0 - 6 AR	1/0 - 8 Sol. 1/0 - 6 AR	25	23	61379-8


Note: Add suffix "9" for prefilled with inhibitor

TYPE DGC DRIVE-ON GROUND CLAMP



CATALOG NUMBER	GROUND ROD SIZE	PIECES/ CARTONS	WT/C	GROUND WIRE SIZE	NAED UPC NO.632591-
DGC-5844*	5/8 (0.555 - 0.565)	50	20	1 or 2 - #4 Sol.	61329-3
DGC-5866*	5/8 (0.555 - 0.565)	30	20	1 or 2 - #6 Sol.	61330-9

CATALOG NUMBER	GROUND ROD SIZE	PIECES/ CARTONS	WT/C	GROUND WIRE SIZE	NAED UPC NO.632591-
DGC-5846	5/8 (0.555 - 0.565)	30	20	1 or 2 - #4 or #6 Sol.	

- For use on all 5/8" diameter UL Listed copper-clad ground rods.
- Used to bond one or two, #4 or #6, solid copper conductors respectively.
- Produced from high-strength copper alloy, the same material as UL Listed "acorn" type ground rod clamps.
- May be used effectively for direct-burial applications.
- To install, the only required tool is a hammer. Compression forces maximize the "direct" surface-to-surface copper contact between conductor and ground rod electrode.
- A drive-head should be used during installation of the ground rod electrode into the soil, thus minimizing any possible mushrooming or deformation on the drive (or chamfer) end of the rod. This will improve ease of installation of the drive-on clamp.
- This design places the grounding conductor in "direct" contact with the ground rod, thereby eliminating multiple paths for the current to follow, which could contribute to increased resistance.
- **Made in USA.** 

To Install:

- **Select the proper connector from the above chart.**
- **Drive the ground rod electrode to the proper depth per national or local code recommendations.**
- **Position connector and ground rod conductors as shown in middle illustration.**
- **Drive connector onto rod until top of connector is flush with top of ground rod as shown in adjacent illustration. Galvan suggests using a 20-ounce hammer.**