

Catalog Number: Item Description: UPC Code: U5169-XTL-100 200A RT OU MAIN 8CRT 784572475458

| Brand Name: | Milbank | | |
|----------------------------|--|--|-----------------------------|
| Туре: | Ring Type | Type Meter Socket | |
| Application: | Meter Soo Center | cket With Main And Load | |
| Standard: | UL Listed | | 8 - |
| Voltage Rating: | Up to 240 Volts Alternating Current | | |
| Amperage Rating: | 200 Continuous Ampere | | |
| Phase: | 1 Phase | | |
| Frequency Rating: | 60 Hertz | | |
| Number Of Cutouts: | 1 | | |
| Cutout Size: | 100 Ampere Main Breaker | | |
| Cable Entry: | Overhead and Underground | | |
| Terminal: | Lay in Line Side and Single Mechanical Load Side | | |
| Mounting: | Surface Mount | | |
| Enclosure: | Type 3R, G90 Galvanized Steel with Powder Coat Finish | | |
| Additional Specifications: | | Number of Jaws:4 Terminal | |
| | Hub Opening and Closing Plates:Twin S | | s:Twin Small Closing Plates |
| | | Hub Opening and Closing Plates:Twin Small Closing Plates | |
| | | Hub Opening and Closing Plates:Twin Small Closing Plates | |
| | | | |

Hub Opening and Closing Plates:Twin Small Closing Plates

Hub Opening and Closing Plates: Twin Small Closing Plates

Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

MILBANK