



Rating		Pin and Sleeve Devices							Accessories	
Amps	Poles and Wires	Configuration Recept./ Plug/ Conn. Inlet	AC Voltage	Connector	Receptacle	HP	Mating Plug**	IP67 Inlet	Back Boxes	Closure Caps
30	2P 3W		125V	HBLS330C4W	HBLS330R4W	2	HBL330P4W	HBL330B4W	BB2030N	PC3430
32	2P 3W		100-130V	HBLS332C4W	HBLS332R4W	2	HBL332P4W	HBL332B4W	BB2030N	PC3430
30	2P 3W		250V	HBLS330C6W*	HBLS330R6W*	5	HBL330P6W*	HBL330B6W*	BB2030N	PC3430
32	2P 3W		220-240V							
30	2P 3W		480V	HBLS330C7W	HBLS330R7W	10	HBL330P7W	HBL330B7W	BB2030N	PC3430
30	3P 4W		125/250V	HBLS430C12W	HBLS430R12W	2	HBL430P12W	HBL430B12W	BB2030N	PC3430
30/32	3P 4W		3Ø 250V	HBLS430C9W*	HBLS430R9W*	10	HBL430P9W*	HBL430B9W*	BB2030N	PC3430
30	3P 4W		3Ø 480V	HBLS430C7W	HBLS430R7W	20	HBL430P7W	HBL430B7W	BB2030N	PC3430
30	3P 4W		3Ø 600V	HBLS430C5W	HBLS430R5W	30	HBL430P5W	HBL430B5W	BB2030N	PC3430
30/32	3P 4W		380-415V	HBLS430C6W*	HBLS430R6W*	7.5	HBL430P6W*	HBL430B6W*	BB2030N	PC3430
32	3P 4W		380-440V	HBLS432C3W	HBLS432R3W	10	HBL432P3W	HBL432B3W	BB2030N	PC3430
30	4P 5W		3ØY 347/600V	HBLS530C5W	HBLS530R5W	30	HBL530P5W	HBL530B5W	BB2030N	PC530
30	4P 5W		200/346- 240/415V	HBLS530C6W*	HBLS530R6W*	7.5	HBL530P6W*	HBL530B6W*	BB2030N	PC530
32	4P 5W		220/380V 240/415V							
30	4P 5W		3ØY 277/480V	HBLS530C7W	HBLS530R7W	20	HBL530P7W	HBL530B7W	BB2030N	PC530
30/32	4P 5W		3ØY 120/208V	HBLS530C9W*	HBLS530R9W*	10	HBL530P9W*	HBL530B9W*	BB2030N	PC530
60	2P 3W		125V	HBLS360C4W	HBLS360R4W	3	HBL360P4W	HBL360B4W	BB60N	PC60
60	2P 3W		250V	HBLS360C6W*	HBLS360R6W*	7.5	HBL360P6W*	HBL360B6W*	BB60N	PC60
63	2P 3W		220-240V							
60	2P 3W		480V	HBLS360C7W	HBLS360R7W	15	HBL360P7W	HBL360B7W	BB60N	PC60
60	3P 4W		125/250V	HBLS460C12W	HBLS460R12W	3	HBL460P12W	HBL460B12W	BB60N	PC60
60/63	3P 4W		3Ø 250V	HBLS460C9W*	HBLS460R9W*	10	HBL460P9W*	HBL460B9W*	BB60N	PC60
60	3P 4W		3Ø 480V	HBLS460C7W	HBLS460R7W	30	HBL460P7W	HBL460B7W	BB60N	PC60
60	3P 4W		3Ø 600V	HBLS460C5W	HBLS460R5W	40	HBL460P5W	HBL460B5W	BB60N	PC60
60/63	3P 4W		380-415V	HBLS460C6W*	HBLS460R6W*	10	HBL460P6W*	HBL460B6W*	BB60N	PC60
60	4P 5W		3ØY 347/600V	HBLS560C5W	HBLS560R5W	40	HBL560P5W	HBL560B5W	BB60N	PC60
60/63	4P 5W		200/346- 240/415V	HBLS560C6W*	HBLS560R6W*	10	HBL560P6W*	HBL560B6W*	BB60N	PC60
60	4P 5W		3ØY 277/480V	HBLS560C7W	HBLS560R7W	30	HBL560P7W	HBL560B7W	BB60N	PC60
60/63	4P 5W		3ØY 120/208V	HBLS560C9W*	HBLS560R9W*	10	HBL560P9W*	HBL560B9W*	BB60N	PC60

Note: *Certain IEC configurations allow for a single product to be certified as both a North American (Series 2) and International amperage (Series 1). These products are marked accordingly with both the UL Listing and UL Classified markings.

**Mating plug or inlet required to maintain 4X/IP69k ratings when used with ADVANTAGE™ series connections.

ADVANTAGE™ series receptacles have the same mounting pattern as standard Hubbell IEC pin and sleeve.

See page G-28 for back boxes and G-29 for accessories.