

151-01474



Article Number: 151-01474

Description: Ratchet P Clamp, 0.76"-1.42" Bundle Dia., 180° Short Length, 0.327" Hole Dia., PA66HIRHSUV, Blk, 160/carton

Base Data	Local Order Number	151-01474
	Type	RCC180SM8
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• One-piece ratchet closure design allows for easy installation during pre- or final assembly.</li> <li>• Four sizes and multiple configurations handle a wide range of diameters and applications, reducing part inventory.</li> <li>• Clamp interior is designed to guide and center bundle to reduce pinching.</li> <li>• Easy release feature allows for quick adjustments and maintenance.</li> <li>• Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.</li> <li>• Steel mounting plate tolerates high torque mounting and is treated to resist chemicals and salt spray.</li> <li>• Soft material inserts are available for sensitive bundles.</li> <li>• For pre-determined clamp pressure, a Tension Tab is available for use with our EVO Series hand tools.</li> </ul>
	Quantity Per	bag
	Product Description	<p>The Ratchet P Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter.</p> <p>The release feature provides easy and nondestructive removal of cables by simply using a flat head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws. The Ratchet P Clamp is offered in four sizes and in multiple mounting configurations.</p>
	Short Description	Ratchet P Clamp, 0.76"-1.42" Bundle Dia., 180° Short Length, 0.327" Hole Dia., PA66HIRHSUV, Blk, 160/carton
Product Dimensions	Minimum Tensile Strength (Imperial)	100.0lbs
	Minimum Tensile Strength (Metric)	445.0N
	Length L (Imperial)	6.15"
	Length L (Metric)	156.1mm
	Length L2 (Imperial)	4.06"
	Length L2 (Metric)	103.0mm
	Variant	180° Short

151-01474



Product Dimensions	Width W (Imperial)	1.37"
	Width W (Metric)	34.9mm
	Cable Tie Width Max. (Imperial)	0.52
	Cable Tie Width Max. (Metric)	13.2mm
	Width W2 (Imperial)	1.181"
	Width W2 (Metric)	30.0mm
	Bundle Diameter Min. (Imperial)	0.76"
	Bundle Diameter Min. (Metric)	19.4mm
	Bundle Diameter Max. (Imperial)	1.42"
	Bundle Diameter Max. (Metric)	36.0mm
	Mounting Hole Diameter D (Imperial)	0.327"
	Mounting Hole Diameter D (Metric)	8.31 mm
	Mounting Hole Centers (Imperial)	2.45"
	Mounting Hole Diameter D Max. (Metric)	8.31mm
Mounting Hole Diameter D Min. (Metric)	8.31mm	
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL94 HB
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Stamping Material	Steel (ST)
Logistic and Packaging		
	Package Quantity	160
	Package Quantity (Metric)	160
	Customs Number(Schedule B)	3926909987