

Eaton T20P11S3716

Catalog Number: T20P11S3716

Eaton General purpose ventilated transformer, Aluminum windings, NEMA 2, FR843A, 60 Hz, 220°C, 37.5 kVA, Single-phase, 240X480V, 120Y/240 Vac, NEMA ST-20, 1 at +5%, 2 at -5% x 2 at +2.5%, 4 at -2.5%, 150°C, 37.5 kVA, 3XA, DOE 2016



Photo is representative

General specifications

Product Name	Catalog Number
Eaton General purpose ventilated transformer	T20P11S3716
	UPC
	786680147630
Product Length/Depth	Product Height
24 in	40 in
Product Width	Product Weight
23.5 in	302 lb
Warranty	Compliances
Eaton Selling Policy 25-000, one (1) year DOE2016 Efficient from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	Certifications
	UL Listed
	OSHPD Certified
	Catalog Notes
	10 CFR Part 431 (2016) Efficient

Physical Attributes

Coil material

Aluminum

Enclosure

NEMA 2

Frame

FR843A

Insulation

220 °C

Mounting

Floor or wall, upright only

Tap size

1 at +5%, 2 at -5% x 2 at +2.5%, 4 at -2.5%

Type

Energy-efficient ventilated type DS-3 transformer

Wiring connection

3XA

Miscellaneous

Weathershield

WS43A

Performance Ratings

Efficiency

10 CFR Part 431-2016 (DOE 2016)

Frequency rating

60 Hz

Kva Rating

37.50 kVA

Primary voltage

240 V, 480 V

Secondary Voltage

120Y/240 V

Sound Level

NEMA ST-20

Temperature rise

150 °C rise

Volt ampere rating

37.5 kVA

Voltage rating

240 X 480 Vac-120Y/240 Vac

Resources

Brochures

[Eaton's high-efficiency dry-type transformers](#)

[Eaton's low-voltage dry-type distribution transformers](#)

Specifications and datasheets

[Eaton Specification Sheet - T20P11S3716](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)