

Eaton DPF221RP

Catalog Number: DPF221RP

Eaton air conditioning disconnect, Fused pullout, 30 A, 120/240V, 10 kAIC, #14-3 Cu/Al 60°C or 75°C, NEMA 3R Galvanized Steel enclosure, 1.5 hp at 120V, 3 hp at 240V, ANSI 61 gray



General specifications

Product Name

Eaton air conditioning disconnect

Catalog Number

DPF221RP

UPC

782114103210

Product Length/Depth

5.4 in

Product Height

8.7 in

Product Width

3.15 in

Product Weight

2.75 lb

Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications

CSA Certified
UL Listed

Catalog Notes

Packaged for retail sale

Type

Fused pullout

Amperage Rating

30A

Horsepower

1.50 hp at 120 V, 3 hp at 240 V

Voltage rating

120/240 V

Wire size

#14-3 AWG Cu/Al

Color

ANSI 61 gray

Enclosure

NEMA 3R

Enclosure material

Galvanized steel

Interrupt rating

10 kAIC

Brochures

[Air Conditioning Disconnects](#)

Catalogs

[Eaton's Volume 1—Residential and Light Commercial](#)

Drawings

[Dimensional Drawing - SKT 200A 1P HCP](#)

Specifications and datasheets

[Eaton Specification Sheet - DPF221RP](#)

Warranty guides

[Selling Policy 25-000 - Distribution and Control Products and Services](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)