

OVERVIEW

Made with the same premium components used on all DP Series controls, the 1704 configuration provides the features most often selected by utilities, making the 1704 our most popular control. Due to its high volume and limited variation, the manufacturing of the 1704 is extremely efficient.

FEATURES

APPLICATIONS

- Roadway & Area Lighting
- Silicon Light Sensor
- Custom Designed Sealed Relay
- MOV Rated for 320 Joule/9500 Amp
- Neoprene Base Gasket has a continuous use temperature of 105°C
- Built In 2 - 5 second turn-off delay
- Brown Polypropylene Cover
- Brass Legs
- Not approved for use on LED fixtures

SPECIFICATIONS

REGULATORY LISTINGS

- ANSI C136.10-1996 Compliant
- ROHS compliant

OPERATING CHARACTERISTICS

- Voltage 105 to 305 VAC, 50/60Hz
- Load rating: 1000 watts, 1800 VA ballast
- -40 to +70°C ambient

Warranty

Eight-year limited warranty. Complete warranty terms located at:
www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application.
 Specifications subject to change without notice.

AcuityControls


DTL®

DP 1704 Utility Preferred

Electronic Locking Type Photocontrol



DIMENSIONS



ORDERING INFORMATION

DP 1704 PHOTOCONTROL			Example: DP124 1.5 1704 J50
Series & Voltage	Turn-On Level (fc)	Utility	Pkg. Qty.
DP124 120-277V	1.5 ANSI Standard	1704	J12 12 Units J50 50 Units