



Ref. Certif. No.

HU-003699-M1

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME**CB TEST CERTIFICATE**

Product	AC Contactor
Name and address of the applicant	Schneider Electric Industries SAS 35 rue Joseph Monier 92500 Rueil-Malmaison, France
Name and address of the manufacturer	Schneider Electric Industries SAS 35 rue Joseph Monier 92500 Rueil-Malmaison, France
Name and address of the factory	Schneider Electric Industries S. A. ZAC Le Village 27100 Le Vaudreuil, France
Ratings and principal characteristics	Ui:690V; Uimp:6kV; Ith:40...50A; Utilization category: AC-3, AC-4, AC-3e; Ue:AC230...690V; Ie:14,2...38A; with electronic coils (See appendix of CB Test Certificate for further ratings)
Trademark (if any)	Schneider Electric
Customer's Testing Facility (CTF) Stage used	N/A
Model / Type Ref.	LC1D25 , LC2D25 , LC1D32 , LC2D32 , LC1D38 , LC2D38
Additional information (if necessary may also be reported on page 2)	This Certificate is Modification No.1 to CBTC ref. No. HU-003699, dated 2021-11-26, and is issued due to adding parameter.
A sample of the product was tested and found to be in conformity with	IEC 60947-4-1:2018 IEC 60947-5-1:2016
As shown in the Test Report Ref. No. which forms part of this Certificate	CN21T9OU 002

This CB Test Certificate is issued by the National Certification Body

**TÜVRheinland**<sup>®</sup>TÜV Rheinland InterCert Kft., MEEI Division  
H-1143 Budapest, Gizella út 51-57., Hungary  
Web:www.tuv.com

Date: 2022-05-27

Signature:

Wencai Zhang



Ref. Certif. No.

HU-003699-M1

Appendix to CB Test Certificate, page 1/1

Type designation:

<u>LC1</u>	<u>D25</u>	<u>6</u>	<u>KUE</u>
(1)	(2)	(3)	(4)

Possible values:

- (1): Basic product type:  
LC1: single contactor  
LC2: reversing contactor
- (2): Size:  
D25  
D32  
D38
- (3): Type of connection:  
Blank: Screw connection  
6: Ring lug connection
- (4): Coil codes: see below table

Coil code tables:

Coil code	Us(V)	Frequency
BNE	24-60	50/60Hz and dc
EHE	48-130	50/60Hz and dc
KUE	100-250	50/60Hz and dc

Ratings:

Model	Ith	Utilization category	Ue				
			230V	400V	440V	500V	690V
LC1D25, LC2D25	40A	Ie(AC-3)	20A	22A	25A	23A	17A
		Ie(AC-4)	16,7A	18,34A	20,84A	19,2A	14,2A
		Ie(AC-3e)	20A	22A	25A	23A	17A
LC1D32, LC2D32	50A	Ie(AC-3)	27A	29A	32A	28A	21A
		Ie(AC-4)	22,5A	24,2A	20,84	19,2	14,2
		Ie(AC-3e)	27A	29A	32A	28A	21A
LC1D38, LC2D38	50A	Ie(AC-3)	31,7A	35A	38A	28A	21A
		Ie(AC-4)	26,42A	29,2A	20,84	19,2	14,2
		Ie(AC-3e)	31,7A	35A	38A	28A	21A

Additional information (if necessary)

Date: 2022-05-27

Signature: Wencai Zhang