

Eaton M1GB2SR2HS

Catalog Number: M1GB2SR2HS

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' 1.5" pipe (Fbrgls univsl sect), Silicone rubber, Stl-2 pt lft, Lightning arrester brkts, ice shields, Horizontal upright (G095 spacing), Torsional

General specifications



Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1GB2SR2HS
	UPC
	194006015097
Product Length/Depth	Product Height
106 in	23.9 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std 1247
	IEEE Std C37.34

Description	Electrical Ratings
Control rod and mechanism 28' 1.5" pipe (fiberglass universal section)	Amperage Rating 900A
Crossarm material Steel - two point lift	Basic impulse level 110 kV
Insulator bolt pattern 2.25" BC	Number of phases Three-phase
Material type Silicone rubber	Voltage rating 15.5 kV
Switch type M-Force switch	

M-Force Switch

- [M-force - optional configurations](#)
Lightning arrester brkts, ice shields
- [Mounting configuration \(M-force only\)](#)
Horizontal upright (G095 spacing)
- [Operating handle configuration \(M-force only\)](#)
Torsional

Resources

- [Brochures](#)
M-Force Three-Phase Switch Catalog
- [Specifications and datasheets](#)
Eaton Specification Sheet - M1GB2SR2HS