



# Ceramalux ALTO Non-Cycling

## C250S50/ALTO NC HPS 1/12PK

Philips Ceramalux High Pressure Sodium Non-Cycling Lamps are a better value than standard high pressure sodium lamps, with longer life and reduced maintenance cost.

#### **Product data**


General Information			
Cap-Base	E39 [Single Contact Mogul Screw]		
Operating Position	UNIVERSAL [Any or Universal (U)]		
Features	ALTO® Non-Cycling		
Light Technical			
Chromaticity Coordinate X (Nom)	0.523		
Chromaticity Coordinate Y (Nom)	0.415		
Correlated Color Temperature (Nom)	2100 K		
Luminous Efficacy (Rated) (Min)	102 lm/W		
Luminous Efficacy (rated) (Nom)	114 lm/W		
Color rendering index (CRI)	21		
Operating and Electrical			
Power Consumption	251 W		
Lamp Current (Nom)	1.8 A		
Voltage (Nom)	100 V		
Voltage (Nom)	100 V		

Mechanical and Housing		
Bulb Finish	Clear	
Bulb Material	Hard Glass	
Bulb Shape	ED18	
Approval and Application		
Mercury (Hg) Content (Nom)	3.36 mg	
Product Data		
Order product name	C250S50/ALTO NC HPS 1/12PK	
Full product name	C250S50/ALTO NC HPS 1/12PK	
Order code	928601156190	
Material Nr. (12NC)	928601156190	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	046677467340	
Numerator - Packs per outer box	12	
EAN/UPC - Case	50046677467345	

Datasheet, 2024, February 19 data subject to change

## **Ceramalux ALTO Non-Cycling**

### Dimensional drawing



Product	D	L	C (max)
C250S50/ALTO NC HPS 1/12PK	2.25 inch	5.750 inch	9.75 inch



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.