

Ground Fault Products Replacement GFCI Module

HUBBELL

Features

- Power Protection Products
- Commercial Spider
- 20A 125V

Ordering Information

Description	Color	UPC	Catalog Number
Hubbell Wiring Device Kellems, GFCI Circuit Breaker, Two Pole, 25A 240V AC, Single Phase	Black	783585580517	HBLCGFM20



Listings

UL Listed - Canadian and U.S.
Meets ADA Standards
Meets all NEC® requirements
CSA Certified
NEMA® WD-6 Compliant

Specifications

1. Class A GFCI, 4-6 mA trip level.
2. Operating temperature range: -35°C to +66°C.
3. Power "on" indication: LED.
4. Ground monitor: Lamp indicator.
5. Approvals: UL Recognized Component file E168173
Series No. 304015XX
6. Over voltage trip level: 170 VAC Maximum.
7. Rating: 120 VAC 60Hz 20A.
8. Insulation voltage: 1500 VRMS – 1 min.
9. Connections:
Input: Lead wire, black (L), white (N), 12AWG stranded 105C, 300V min.
Output: Lead wire, black (L), white (N), 12AWG stranded 105C, 300V min.
10. Enclosure color: Black
11. Phillips head screw bolt (#8-32 x 25/8" long) with matching lock nuts – 2 sets (included).

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

