

CERTIFICATION


Applicant : American Power Conversion Holding Inc. Taiwan Branch
Address : 3F., No. 205, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan R.O.C.
Manufacturer : American Power Conversion Holding Inc. Taiwan Branch
Address : 3F., No. 205, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan R.O.C.
Description of EUT : Uninterruptible Power System
Trade Name : APC
Model Number : BR1000MS
Product Series : BR1000MXXXXXXXXXX("X" can be 0-9, A-Z, "-" or blank)
Type of Test : FCC Part 15 Subpart B
Technical Standard : **Emission**
FCC Part 15 Subpart B Class B
CISPR 22 : 2008 Class B
ANSI C63.4 : 2014
Report Number : HA170681-FD
Receipt Date : 29-JUN-2017
Issue Date : 21-JUL-2017
Test Result : **Compliance**

The above equipment was tested by *HongAn TECHNOLOGY CO., LTD.*, for compliance with the requirement set forth in the FCC Rules and Regulation Part 15, Subpart B and the measurement procedures were based on ANSI C63.4.

Note :

1. The results of the test report relate only to the sample tested.
2. The test report shall not be reproduced without the written approval of *HongAn TECHNOLOGY CO., LTD.*

Approved by:



Adam Yang / Section Manager



HongAn TECHNOLOGY CO., LTD.

HongAn TECHNOLOGY EMC Laboratory

NO.15-1, CWEISHUH KENG, CWEIPIN VILLAGE,

LINKOU DIST, NEW TAIPEI CITY, TAIWAN, R.O.C.

TEL : +886-2-26030362

FAX : +886-2-26019259

E-mail : hatlab@ms19.hinet.net

BSMI Registration No. : SL2-IN-E-0023, SL2-IS-E-0023,
SL2-A1-E-0023, SL2-R1-E-0023,
SL2-R2-E-0023, SL2-L1-E-0023

FCC Designation No. : TW1071, TW1163

TAF Accreditation No. : 1163

VCCI Registration No. : R-2156, C-2329, T-219, G-696



FCC COMPLIANCE TEST REPORT

Technical Statement of Conformity
in accordance with FCC Part 15 Subpart B

The Product

Equipment Under Test	: Uninterruptible Power System
Model Number	: BR1000MS
Product Series	: BR1000MXXXXXXXXXX ("X" can be 0-9, A-Z, "-" or blank)
Report Number	: HA170681-FD
Issue Date	: 21-JUL-2017
Test Result	: Compliance

is produced by
American Power Conversion Holding Inc. Taiwan Branch
3F., No. 205, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan R.O.C.



HongAn TECHNOLOGY CO., LTD.
HongAn TECHNOLOGY EMC Laboratory

NO.15-1, CWEISHUH KENG, CWEIPIN VILLAGE,
LINKOU DIST, NEW TAIPEI CITY,
TAIWAN, R. O. C.

TEL: +886-2-26030362
FAX: +886-2-26019259
E-mail: hatlab@ms19.hinet.net

BSMI Registration No.: SL2-IN-E-0023, SL2-A1-E-0023,
SL2-IS-E-0023, SL2-R1-E-0023,
SL2-R2-E-0023, SL2-L1-E-0023

FCC Designation No.: TW1071, TW1163
TAF Accreditation No.: 1163
VCCI Registration No.: R-2156, C-2329, T-219, G-696



Contents

1	General Description	5
1.1	Description of Equipment Under Test	5
1.2	Test Facility	6
1.3	Test Instruments	6
1.4	Test Methodology	7
1.5	Auxiliary Equipments	7
1.6	Block Diagram	8
1.7	Identifying the Final Test Mode	8
1.8	Final Test Mode	8
1.9	Condition of Power Supply	8
1.10	EUT Configuration	8
2	Conducted Emission Test	9
2.1	Test Instruments	9
2.2	Test Configuration and Procedure	9
2.3	Conducted Limit	10
2.4	Test Result	10
3	Radiated Emission Test – Below 1 GHz	15
3.1	Test Instruments	15
3.2	Test Configuration and Procedure	15
3.3	Radiated Limit	16
3.4	Test Result	16
4	Radiated Emission Test – Above 1GHz	21
4.1	Test Instruments	21
4.2	Test Configuration and Procedure	21
4.3	Test Limit	22
4.4	Test Result	22
5	Photographs of Test	23
5.1	Conducted Emission Test	23
5.2	Radiated Emission Test – Below 1 GHz	24
6	Photographs of EUT	25

Verification

Applicant : American Power Conversion Holding Inc. Taiwan Branch

Manufacturer : American Power Conversion Holding Inc. Taiwan Branch

Equipment Under Test : Uninterruptible Power System

Model Number : BR1000MS

Product Series : BR1000MXXXXXXXXXXXX("X" can be 0-9, A-Z, "-" or blank)

Sample Received Date : 29-JUN-2017

Test Standards :

Emission :

FCC Part 15 Subpart B Class B
CISPR 22 : 2008 Class B
ANSI C63.4 : 2014

Remark

This report details the results of the test carried out on one sample. The test results are contained in this test report and HongAn Technology Co., Ltd. assumes full responsibility for the accuracy and completeness of these tests. This report shows the EUT is technically compliant with FCC Part 15 Subpart B and CISPR 22 Class B official requirements. The test procedure is in compliance with ANSI C63.4. This report applies to the above sample only and shall not be reproduced in part without written approval of HongAn Technology Co., Ltd.

Documented by:

Mindy Liu

Date: 21-JUL-2017

Mindy Liu / ADM. Dept. Staff

Tested by:

Tom Tang

Date: 20-JUN-2017

Tom Tang / ENG. Dept. Staff

Approved by:

Adam Yang

Date: 21-JUL-2017

Adam Yang / SEC. Manager



Summary of Test Result

Emission			
Test Standard	Test Item	Test Result	Remark
FCC Part15 Subpart B CISPR22 Class B ANSI C63.4	Conducted Emission	Pass	Highest Emission -LINE Mode L:7.14MHz, A.V.37.20dBuV,Margin -12.80 dBuV N:1.14MHz, A.V.35.56dBuV,Margin -10.44 dBuV Highest Emission- Battery mode L:4.20MHz, A.V.32.69dBuV,Margin -23.31 dBuV N:4.34MHz, A.V.23.60dBuV,Margin -22.40 dBuV
FCC Part15 Subpart B CISPR22 Class B ANSI C63.4	Radiated Emission (Below 1GHz)	Pass	Highest Emission -LINE Mode H: 191.92MHz, 22.16dBuV, Margin -7.84 dB Antenna Height 393 cm, Turntable Angle 92° V: 51.20MHz, 26.68dBuV, Margin -3.32 dB Antenna Height 102cm, Turntable Angle 211° Highest Emission -Battery mode H: 64.29MHz, 22.23dBuV, Margin -7.77 dB Antenna Height 400 cm, Turntable Angle 162° V: 65.45MHz, 26.04dBuV, Margin -3.96 dB Antenna Height 101cm, Turntable Angle 87°
FCC Part15 Subpart B CISPR22 Class B ANSI C63.4	Radiated Emission (Above 1GHz)	N/A	The highest frequency of the internal sources of the EUT is less than 108MHz, the measurement shall only be made up to 1GHz. Hence, the test item is not required.

Measurement Uncertainty

The following measurement uncertainty has been calculated for Emission Tests performed on the EUT as specified in CISPR 16-4-2:

Test Item		Uncertainty
Conducted Emission		± 4.35dB
Radiated Emission	Below 1GHz	± 5.64dB
	Above 1GHz	± 4.91dB

This reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95%.

1 General Description

1.1 Description of Equipment Under Test

Equipment Under Test	:	Uninterruptible Power System
Model Number	:	BR1000MS
Product Series	:	BR1000MXXXXXXXXXX("X" can be 0-9, A-Z, "-" or blank)
Applicant	:	American Power Conversion Holding Inc. Taiwan Branch
Address of Applicant	:	3F., No. 205, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan R.O.C.
Manufacturer	:	American Power Conversion Holding Inc. Taiwan Branch
Address of Manufacturer	:	3F., No. 205, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan R.O.C.
Power Supply	:	AC 120V <input type="checkbox"/> Shielded <input checked="" type="checkbox"/> Non-Shielded <input type="checkbox"/> Detachable, m <input checked="" type="checkbox"/> Un-Detachable, 1.8m <input type="checkbox"/> w Ferrite Core <input checked="" type="checkbox"/> w/o Ferrite Core
I/O Port	:	USB Type (A*1+C*1) or A*2, Gigabit*2, Surge*4, Battery+Surge*6, Cable In *1, Cable Out *1, Data port*1.
Data Cable	:	<input checked="" type="checkbox"/> Data Cable <input checked="" type="checkbox"/> Shielded <input type="checkbox"/> Non-Shielded <input checked="" type="checkbox"/> Detachable, 1.8m <input type="checkbox"/> Un-Detachable <input checked="" type="checkbox"/> w Ferrite Core*1 <input type="checkbox"/> w/o Ferrite Core <input checked="" type="checkbox"/> Coaxial Cable <input checked="" type="checkbox"/> Shielded <input type="checkbox"/> Non-Shielded <input checked="" type="checkbox"/> Detachable, 0.9m <input type="checkbox"/> Un-Detachable <input type="checkbox"/> w Ferrite Core <input checked="" type="checkbox"/> w/o Ferrite Core
Description of EUT	:	Dimensions :368 cm (L) X 1000 cm (W) X 2600 cm (H) Highest Frequency of the Internal Source : less than 108MH Position : <input checked="" type="checkbox"/> Table-top / <input type="checkbox"/> Floor-standing Intended Function : The EUT is a Uninterruptible Power System. Product Variance : The EUT is the most advanced model within the series. HongAn is only responsible for the test result of the main test sample.



1.2 Test Facility

All the Conducted and Radiated Emission Tests are performed at No. 15-1, Cweishuh Keng, Cweipin Village, Linkou, New Taipei City, Taiwan, R.O.C.

1.3 Test Instruments

1.3.1 Instruments Used for Emission Measurement

Instrument Name	Manufacture	Model Number	Serial Number	Last Cal. Date	Next Cal. Date
LISN	EMCO	3810/2NM	9702-1819	07-Mar-2017	07-Mar-2018
LISN	Rolf Heine Hochfrequenz- technik	NNB-4/32T	00001	08-Mar-2017	08-Mar-2018
RF Current Probe	FCC	F-33-4	53	26-May-2017	26-May-2018
Impedance Stabilization Network (ISN)	TESEQ	ISN T800	30838	18-Aug-2016	18-Aug-2017
EMI Receiver	R&S	ESCI	100931	21-Jul-2016	21-Jul-2017
Spectrum Analyzer	R&S	FSV 30	101629	11-Jan-2017	11-Jan-2018
Preamplifier	CHASE	CPA 9231A	0405	24-Aug-2016	24-Aug-2017
Preamplifier	HD	HD17187	004	22-May-2017	22-May-2018
Bilog Antenna	TESEQ	CBL6111D	25769	13-Feb-2017	13-Feb-2018
Bilog Antenna	TESEQ	CBL6111D	38521	18-Oct-2016	18-Oct-2017
Double-Ridged Waveguide Horn	EMCO	3115	9912-5992	22-May-2017	22-May-2018

※ The test equipments used are calibrated and can be traced to National ITRI and International Standards.

1.4 Test Methodology

All Conducted and Radiated Emission Tests were performed according to the procedures stated in ANSI C63.4 as indicated in FCC Part 15 Subpart B Sec. 15.31.

Deviations from the test standards as below description : N/A

1.5 Auxiliary Equipments

1.5.1 Provided by HongAn Technology Co., Ltd. for Emission Test.


No.	Equipment	Model No.	Serial No.	EMC Approved	Brand	Description	
						Data Cable	Power Cable
01	Notebook	PP2090	CNU3480M1R	CE Mark, FCC DoC, BSMI ID R33001	Hewlett Packard	N/A	AC to Adapter Unshielded*1.8m Adapter to Notebook Unshielded*1.8m
02	Notebook	G42-352TX	CNF0347B16	CE Mark, FCC DoC, BSMI ID R33001	Hewlett Packard	N/A	AC to Adapter Unshielded*1m Adapter Notebook Unshielded*1.8m with EMI core*1
03	Notebook	X553M	N/A	CE Mark, FCC DoC, BSMI ID R31018	ASUS	N/A	N/A
04	LAMP	40W	N/A	N/A	N/A	N/A	N/A
05	LAMP*2	250W	N/A	N/A	N/A	N/A	N/A
06	USB Type -C&A Cable	N/A	N/A	N/A	N/A	Shielded; Detachable, 1 m; w/o Ferrite Core	N/A
07	Gigabit Cable*2	N/A	N/A	N/A	N/A	Shielded; Detachable, 3 m; w/o Ferrite Core	N/A
08	Power Cable*10	N/A	N/A	N/A	N/A	N/A	Non-Shielded; Detachable, 1.8m w/o Ferrite Core

1.5.2 Provided by the Manufacturer

N/A



1.6 Block Diagram



1.7 Identifying the Final Test Mode

1. Line mode (Full load).
2. Battery mode (Full load).

Note: The additional power cords do not increase the disturbance level by 2dB. Therefore, the Final EMC Assessment was performed for the Line mode and Battery mode.

1.8 Final Test Mode

1. Line mode (Full load).
2. Battery mode (Full load).

1.9 Condition of Power Supply

AC 120V; 60Hz

1.10 EUT Configuration

1. Setup the EUT and peripheral as shown in Section 1.6.
2. Turn on the power of all equipments.
3. Activate the selected Final Test Mode shown in Sec. 1.8.

2 Conducted Emission Test

2.1 Test Instruments

Refer to Sec. 1.3 Test Instruments.

2.2 Test Configuration and Procedure




Table-top Equipment

- The EUT was placed on a non-conductive table which was 80 cm above the horizontal coupling plane. The rear of the EUT was 40 cm from the vertical coupling plane.
- The excess interface cables were folded at the cable center into a bundle no longer than 40 cm, so that the bundles were on the table.
- The EUT was connected to the main power through a L.I.S.N. This set up provided 50 ohm / 50 μ H coupling impedance for the measuring equipment.
- All auxiliary equipment received power from a second L.I.S.N.
- The conducted emissions were measured between the Line Phase and the PE ground and between the Neutral Phase and the PE ground using an EMI Receiver.
- The values were recorded.



2.3 Conducted Limit

☒ FCC Part 15 B / CISPR 22

Frequency (MHz)	<input type="checkbox"/> Class A		<input checked="" type="checkbox"/> Class B	
	Q.P. (Quasi-Peak)	A.V. (Average)	Q.P. (Quasi-Peak)	A.V. (Average)
0.15 to 0.50	79	66	66 to 56	56 to 46
0.50 to 5.0	73	60	56	46
5.0 to 30	73	60	60	50

2.4 Test Result

PASS

The final tests data are shown on the following page(s).


**Conducted Emission Test Data- Line mode**

Test Date : 18-JUL-2017

Power Line : Line

Temperature : 26°C

Humidity : 56%



No.	Freq MHz	Reading dBuV	C.F dB	Result dBuV	Limit dBuV	Margin dB	Power Line	Remark
1	0.40	27.90	0.15	28.05	47.77	-19.72	LINE	Average
2	0.40	32.90	0.15	33.05	57.77	-24.72	LINE	QP
3	0.51	25.64	0.17	25.81	46.00	-20.19	LINE	Average
4	0.51	33.64	0.17	33.81	56.00	-22.19	LINE	QP
5	0.68	27.16	0.19	27.35	46.00	-18.65	LINE	Average
6	0.68	33.16	0.19	33.35	56.00	-22.65	LINE	QP
7	1.14	30.74	0.22	30.96	46.00	-15.04	LINE	Average
8	1.14	39.60	0.22	39.82	56.00	-16.18	LINE	QP
9	2.08	25.56	0.26	25.82	46.00	-20.18	LINE	Average
10	2.08	32.56	0.26	32.82	56.00	-23.18	LINE	QP
11	7.14	36.63	0.57	37.20	50.00	-12.80	LINE	Average
12	7.14	43.22	0.57	43.79	60.00	-16.21	LINE	QP

- Remark :
1. All readings are Quasi-Peak and Average values.
 2. Result = Reading + C.F
 3. Margin = Result – Limit


Conducted Emission Test Data- Line mode

Test Date : 18-JUL-2017

Power Line : Neutral

Temperature : 26°C

Humidity : 56%



No.	Freq MHz	Reading dBuV	C.F dB	Result dBuV	Limit dBuV	Margin dB	Power Line	Remark
1	0.43	26.62	0.14	26.76	47.20	-20.44	NEUTRAL	Average
2	0.43	32.62	0.14	32.76	57.20	-24.44	NEUTRAL	QP
3	0.73	31.30	0.17	31.47	46.00	-14.53	NEUTRAL	Average
4	0.73	35.71	0.17	35.88	56.00	-20.12	NEUTRAL	QP
5	1.14	35.36	0.20	35.56	46.00	-10.44	NEUTRAL	Average
6	1.14	39.72	0.20	39.92	56.00	-16.08	NEUTRAL	QP
7	1.32	29.83	0.22	30.05	46.00	-15.95	NEUTRAL	Average
8	1.32	35.83	0.22	36.05	56.00	-19.95	NEUTRAL	QP
9	2.06	28.62	0.25	28.87	46.00	-17.13	NEUTRAL	Average
10	2.06	33.17	0.25	33.42	56.00	-22.58	NEUTRAL	QP
11	7.29	29.36	0.53	29.89	50.00	-20.11	NEUTRAL	Average
12	7.29	37.16	0.53	37.69	60.00	-22.31	NEUTRAL	QP

- Remark :
1. All readings are Quasi-Peak and Average values.
 2. Result = Reading + C.F
 3. Margin = Result – Limit


Conducted Emission Test Data- Battery mode

Test Date : 18-JUL-2017

Power Line : Line

Temperature : 26°C

Humidity : 56%



No.	Freq MHz	Reading dBμV	C.F dB	Result dBμV	Limit dBμV	Margin dB	Power Line	Remark
1	0.52	13.84	0.17	14.01	46.00	-31.99	LINE	Average
2	0.52	28.20	0.17	28.37	56.00	-27.63	LINE	QP
3	0.98	19.60	0.21	19.81	46.00	-26.19	LINE	Average
4	0.98	25.36	0.21	25.57	56.00	-30.43	LINE	QP
5	2.20	18.15	0.28	18.43	46.00	-27.57	LINE	Average
6	2.20	28.57	0.28	28.85	56.00	-27.15	LINE	QP
7	2.53	21.63	0.29	21.92	46.00	-24.08	LINE	Average
8	2.53	30.84	0.29	31.13	56.00	-24.87	LINE	QP
9	4.20	21.24	0.38	21.62	46.00	-24.38	LINE	Average
10	4.20	32.31	0.38	32.69	56.00	-23.31	LINE	QP
11	6.99	22.14	0.56	22.70	50.00	-27.30	LINE	Average
12	6.99	30.38	0.56	30.94	60.00	-29.06	LINE	QP

- Remark : 1. All readings are Quasi-Peak and Average values.
 2. Result = Reading + C.F
 3. Margin = Result – Limit


Conducted Emission Test Data- Battery mode

Test Date : 18-JUL-2017

Power Line : Neutral

Temperature : 26°C

Humidity : 56%



No.	Freq MHz	Reading dBuV	C.F dB	Result dBuV	Limit dBuV	Margin dB	Power Line	Remark
1	0.41	18.74	0.14	18.88	47.64	-28.76	NEUTRAL	Average
2	0.41	27.61	0.14	27.75	57.64	-29.89	NEUTRAL	QP
3	0.77	20.54	0.17	20.71	46.00	-25.29	NEUTRAL	Average
4	0.77	26.88	0.17	27.05	56.00	-28.95	NEUTRAL	QP
5	1.86	21.29	0.25	21.54	46.00	-24.46	NEUTRAL	Average
6	1.86	28.29	0.25	28.54	56.00	-27.46	NEUTRAL	QP
7	2.36	17.84	0.27	18.11	46.00	-27.89	NEUTRAL	Average
8	2.36	28.31	0.27	28.58	56.00	-27.42	NEUTRAL	QP
9	4.34	23.23	0.37	23.60	46.00	-22.40	NEUTRAL	Average
10	4.34	26.23	0.37	26.60	56.00	-29.40	NEUTRAL	QP
11	7.14	24.12	0.52	24.64	50.00	-25.36	NEUTRAL	Average
12	7.14	32.16	0.52	32.68	60.00	-27.32	NEUTRAL	QP

- Remark :
1. All readings are Quasi-Peak and Average values.
 2. Result = Reading + C.F
 3. Margin = Result – Limit



3 Radiated Emission Test – Below 1 GHz

3.1 Test Instruments

Refer to Sec. 1.3 Test Instruments.

3.2 Test Configuration and Procedure




Table-top Equipment

- The EUT was placed on a non-conductive turntable which was 80cm above the horizontal ground plane. The EUT was set 10m (or 3m) away from the receiving antenna that was mounted on a non-conductive mast.
- Main cables draped to the ground plane and were routed to the mains power outlet. The mains power outlet was bonded to and did not protrude above the ground plane.
- The antenna was adjusted between 1m and 4m in height above the ground plane and the Antenna-to-EUT azimuth was also varied during the measurements to find the top 6 maximum meter readings within the frequency range limit as indicated in Sec 3.3.
- The radiated emissions were measured when the Antenna-to-EUT polarization was set horizontally and vertically.
- The values were recorded.



3.3 Radiated Limit

☐ FCC Part 15 Subpart B

	<input type="checkbox"/> Class A (10m)		<input type="checkbox"/> Class B (3m)	
Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Quasi-Peak ($\text{dB}\mu\text{V/m}$)	Field Strength ($\mu\text{V/m}$)	Quasi-Peak ($\text{dB}\mu\text{V/m}$)
30 to 88	90	39.0	100	40.0
88 to 216	150	43.5	150	43.5
216 to 960	210	46.5	200	46.0
Above 960	300	49.5	500	54.0

Emission Level ($\text{dB}\mu\text{V/m}$) = $20 \log$ Emission Level ($\mu\text{V/m}$)

Refer to FCC Part 15 Subpart B clause 15.109(g) :

As an alternative to the radiated emission limits shown in paragraphs (a) and (b) of this section, digital devices may be shown to comply with the standards contained in Third Edition of the International Special Committee on Radio Interference (CISPR), Pub. 22, "Information Technology Equipment—Radio Disturbance Characteristics—Limits and Methods of Measurement".

☒ CISPR 22

	<input type="checkbox"/> Class A (10m)	<input checked="" type="checkbox"/> Class B (10m)
Frequency (MHz)	Quasi-Peak ($\text{dB}\mu\text{V/m}$)	Quasi-Peak ($\text{dB}\mu\text{V/m}$)
30 to 230	40.0	30.0
230 to 1000	47.0	37.0

3.4 Test Result

PASS

The final tests data are shown on the following page(s).


**Radiated Emission Test Data- Line mode**

Test Date : 18-JUL-2017

Polarization : Horizontal

Temperature : 26°C

Humidity : 56%



No.	Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Antenna Pol.	Remark
1	30.00	24.00	-4.12	19.88	30.00	-10.12	400	82	HORIZONTAL	QP
2	56.45	33.98	-16.26	17.72	30.00	-12.28	399	117	HORIZONTAL	QP
3	109.32	33.27	-12.00	21.27	30.00	-8.73	397	65	HORIZONTAL	QP
4	144.01	31.70	-11.49	20.21	30.00	-9.79	396	37	HORIZONTAL	QP
5	191.92	35.89	-13.73	22.16	30.00	-7.84	393	92	HORIZONTAL	QP
6	222.03	33.89	-12.98	20.91	30.00	-9.09	391	123	HORIZONTAL	QP

Remark : 1. All readings are Quasi-Peak values.

2. Result = Reading + C.F

3. Margin = Result – Limit


**Radiated Emission Test Data- Line mode**

Test Date : 18-JUL-2017

Polarization : Vertical

Temperature : 26°C

Humidity : 56%



No.	Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Antenna Pol.	Remark
1	31.04	31.01	-4.75	26.26	30.00	-3.74	100	86	VERTICAL	QP
2	51.20	41.70	-15.02	26.68	30.00	-3.32	102	211	VERTICAL	QP
3	107.00	32.10	-12.22	19.88	30.00	-10.12	105	96	VERTICAL	QP
4	144.01	35.27	-11.49	23.78	30.00	-6.22	107	81	VERTICAL	QP
5	191.92	36.83	-13.73	23.10	30.00	-6.90	110	107	VERTICAL	QP
6	220.87	38.00	-13.13	24.87	30.00	-5.13	109	68	VERTICAL	QP


Remark : 1. All readings are Quasi-Peak values.

2. Result = Reading + C.F

3. Margin = Result – Limit

Radiated Emission Test Data- Battery mode

Test Date : 18-JUL-2017 Polarization : Horizontal
 Temperature : 26°C Humidity : 56%



No.	Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Antenna Pol.	Remark
1	64.29	39.14	-16.91	22.23	30.00	-7.77	400	162	HORIZONTAL	QP
2	109.32	31.57	-12.00	19.57	30.00	-10.43	398	87	HORIZONTAL	QP
3	144.00	30.00	-11.49	18.51	30.00	-11.49	395	125	HORIZONTAL	QP
4	191.15	34.22	-13.74	20.48	30.00	-9.52	393	93	HORIZONTAL	QP
5	221.26	33.45	-13.06	20.39	30.00	-9.61	391	77	HORIZONTAL	QP
6	264.87	28.39	-8.73	19.66	37.00	-17.34	392	68	HORIZONTAL	QP

Remark : 1. All readings are Quasi-Peak values.
 2. Result = Reading + C.F
 3. Margin = Result – Limit


**Radiated Emission Test Data- Battery mode**

Test Date : 18-JUL-2017

Polarization : Vertical

Temperature : 26°C

Humidity : 56%



No.	Freq MHz	Reading dBuV	C.F dB	Result dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Antenna Pol.	Remark
1	51.66	39.00	-15.15	23.85	30.00	-6.15	100	77	VERTICAL	QP
2	65.45	42.91	-16.87	26.04	30.00	-3.96	101	87	VERTICAL	QP
3	113.18	35.53	-11.74	23.79	30.00	-6.21	102	162	VERTICAL	QP
4	144.00	32.00	-11.49	20.51	30.00	-9.49	105	113	VERTICAL	QP
5	192.31	34.19	-13.72	20.47	30.00	-9.53	107	158	VERTICAL	QP
6	223.19	35.01	-12.90	22.11	30.00	-7.89	110	91	VERTICAL	QP

- Remark :
1. All readings are Quasi-Peak values.
 2. Result = Reading + C.F
 3. Margin = Result – Limit

4 Radiated Emission Test – Above 1GHz

4.1 Test Instruments

Refer to Sec. 1.3 Test Instruments.

4.2 Test Configuration and Procedure




Table-top Equipment

- The EUT was placed on a non-conductive turntable which was 80cm above the horizontal ground plane. The EUT was set 3m away from the receiving antenna that was mounted on a non-conductive mast.
- Main cables draped to the ground plane and were routed to the mains power outlet. The mains power outlet was bonded to and did not protrude above the ground plane.
- The antenna was adjusted between 1m and 4m in height above the ground plane and the Antenna-to-EUT azimuth was also varied during the measurements to find the top 6 maximum meter readings within the frequency range limit as indicated in Sec 4.3.
- The radiated emissions were measured when the Antenna-to-EUT polarization was set horizontally and vertically.
- The values were recorded.

4.3 Test Limit

FCC Part 15 Subpart B

Frequency GHz	Class A at 10m			Class B at 3m		
	Field Strength ($\mu\text{V/m}$)	Average (dB $\mu\text{V/m}$)	Peak (dB $\mu\text{V/m}$)	Field Strength ($\mu\text{V/m}$)	Average (dB $\mu\text{V/m}$)	Peak (dB $\mu\text{V/m}$)
Above 1GHz	300	49.5	69.5	500	54	74

Note : 1. The lower limit shall apply at the transition frequencies.

2. Emission level (dB $\mu\text{V/m}$) = 20 log Emission level ($\mu\text{V/m}$).

3. The measurement above 1GHz is at close-in 3m, and determine the limit **L2** corresponding to the close-in distance **d2** by applying the following relation: **L2=L1(d1/d2)**, where **L1** is the specified limit in microvolts per meter (**$\mu\text{V/m}$**) at the distance **d1(10m)**, **L2** is the new limit for distance **d2(3m)**.

So the new Class A limit above 1GHz at 3m is as following table:

Frequency GHz	Class A at 3m	
	Average (dB $\mu\text{V/m}$)	Peak (dB $\mu\text{V/m}$)
Above 1GHz	60	80

4.4 Test Result

Not applicable

※The highest frequency of the internal sources of the EUT is less than 108MHz. Hence, above 1GHz Radiated Measurement shall not be made.

5 Photographs of Test

5.1 Conducted Emission Test



Front View




Rear View

5.2 Radiated Emission Test – Below 1 GHz



Front View



Rear View

6 Photographs of EUT



Front View of EUT




Rear View of EUT




Inside View of EUT




Front View of EUT's PCB 1




Rear View of the PCB 1




Front View of the PCB 2



Rear View of the PCB 2



Front View of the PCB 3



Rear View of the PCB 3



Front View of the PCB 4



Rear View of the PCB 4




Front View of the PCB 5



Rear View of the PCB 5



Front View of the PCB 6



Rear View of the PCB 6



View of the EUT Battery



View of the EUT Battery label



View of the Transformer



View of the Transformer label



View of the Coaxial cable



View of the data cable