



Product Number: 74908

Order Abbreviation: SLMFLD1A/030UNV840/WF/BZ

General Description: Slim Floodlight 1A, 30 watts, 120-277V, Dimmable, 80+CRI, 4000K, wide flood distribution, bronze painted finish

Product Information

Power Factor	?0.90
Primary Lamp Type	SMD
Minimum Operating Temperature - Celsius	-40
Minimum Operating Temp - Fahrenheit	-40
Primary Lamp Type 1	SMD
Total Harmonic Distortion (THD)	?20 %
Efficacy (LPW)	110
Abbrev. With Packaging Info.	SLMFLD1A030UNV840WFBZ 1/CS 1/SKU
Color Temperature/CCT (K)	4000
Ordering Abbreviation	SLMFLD1A/030UNV840/WF/BZ
Average Rated Life 1 (hr)	150000
Lumens	3400
Nominal Voltage (V)	120.00
Nominal Wattage (W)	30.00
UPC Code	UPC046135749087
Color Rendering Index (CRI)	>80
Service Life Rating	?150000
Lumens (lm)	3400
Wattage (W)	30.00
Color Range	4000 K
Connectors	Wire nuts
Energy Star Rated	No
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	Bronze
Luminaire Type	Flood light
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Power Input	30
Dimensions	9.06x1.57x10.47
Certification Listing	cULus, FCC, RoHS, DLC