# HellermannTyton

### 181-92010

Article Number: 181-92010

Wiring Duct Cover for 2" Duct, 6 ft Long, PVC, White 30ft/Box

## HellermannTyton

RoHS



#### Base Data

| Local Order Number    | 181-92010  |
|-----------------------|--|
| Туре                  | TC2  |
| Color                 | White (WH)   |
| Features and Benefits | <ul> <li>A temporary film is applied to the covers to protect against scratches and is writable for identification during<br/>installation.</li> </ul>   |
|                       | <ul> <li>Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.</li> <li>Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)</li> </ul> |
| Product Description   | HellermannTyton's Pro-Duct wiring duct covers are sold separately and interchangeable among the 3 styles of duct (solid, slotted and high density). Manufactured from high impact, rigid PVC, Pro-Duct covers come in standard colors of white, gray and black. Wiring duct covers are available in 6 foot lengths.              |
| Short Description     | Wiring Duct Cover for 2" Duct, 6 ft Long, PVC, White 30ft/Box  |

#### **Product Dimensions**

| Length L (Imperial) | 6.0 ft  |
|---------------------|---------|
| Length L (Metric)   | 1.83 m  |
| Width W (Imperial)  | 2.0 "   |
| Width W (Metric)    | 50.8 mm |
|                     |         |

#### Logistics and Packaging

| Quantity Per              | box      |
|---------------------------|----------|
| Package Quantity          | 30.0 ft  |
| Package Quantity (Metric) | 9.1 m    |
| Carton Quantity           | 120.0 ft |
|                           |          |

#### **Material and Specifications**

| Material                    | Polyvinylchloride (PVC) |
|-----------------------------|-------------------------|
| Material Shortcut           | PVC                     |
| Flammability                | self-extinguishing      |
| Operating Temperature       | +122°F (+50°C)          |
| <b>ROHS</b> Compliant       | Yes                     |
| Certification/Specification | UL<br>CSA               |
| UL Listed (US and Canada)   | No                      |
| UL Recognized (US)          | Yes                     |

© HellermannTyton 2015