

## USB Charger Receptacles and Outlets

### Wireless Chargers

Description	Color	Rating	Receptacle	Catalog Number
Wireless wall mount phone charger	White	Coil: 7.5 watt inductive, 125V AC input	-	<b>USB1518</b>



### Combination Wireless Chargers

Description	Color	Rating	Receptacle	Catalog Number
Combination wireless wall mount phone charger, inductive coil with USB Type A&C ports, and tamper-resistant receptacle	White	Coil: 7.5 watt inductive, USB: 5A 5V DC Input: 125V AC	15A 125V 20A 125V	<b>USB1528AC</b> <b>USB2028AC</b>



### USB-C Power Delivery Charger

#### Tamper-Resistant Duplex Receptacles

Description	Color	15A 125V	20A 125V
Type-C USB Power Delivery Charger Receptacle, two Type-C port configurations, one USB-C Power Delivery port with up to 55 Watt output and one USB Type-C convenience port with up to 1.5 Amp, 5 Volt USB output.	Black	<b>USB15CPDBK</b>	<b>USB20CPDBK</b>
	Brown	<b>USB15CPD</b>	<b>USB20CPD</b>
	Gray	<b>USB15CPDGY</b>	<b>USB20CPDGY</b>
	Ivory	<b>USB15CPDI</b>	<b>USB20CPDI</b>
	Light Almond	<b>USB15CPDLA</b>	<b>USB20CPDLA</b>
Type A&C USB Power Delivery Charger Receptacle, one Type-A and one Type-C port configurations, one USB-C Power Delivery port with up to 55 Watt output and one USB-A convenience port with up to 1.5 Amp, 5 Volt USB output.	Black	<b>USB15ACPDBK</b>	<b>USB20ACPDBK</b>
	Brown	<b>USB15ACPD</b>	<b>USB20ACPD</b>
	Gray	<b>USB15ACPDGY</b>	<b>USB20ACPDGY</b>
	Ivory	<b>USB15ACPDI</b>	<b>USB20ACPDI</b>
	Light Almond	<b>USB15ACPDLA</b>	<b>USB20ACPDLA</b>
White	<b>USB15ACPDW</b>	<b>USB20ACPDW</b>	



**USB1528AC**



**USB15CPDW**



**USB15ACPDW**

Note: See page Tech-10 for Tamper-Resistant description.  
See section L for Hospital grade series.



### 4 Port USB Charger Outlets

Description	Color	4 Type A ports	2 Type A and 2 Type-C ports	4 Type-C ports
USB Charger Outlets, 4 USB ports, 5 Amp, 5 Volt DC, Style Line® decorator.	Black	<b>USB4BK</b>	<b>USB4ACBK</b>	<b>USB4CBK</b>
	Brown	<b>USB4</b>	<b>USB4AC</b>	<b>USB4C</b>
	Gray	<b>USB4GY</b>	<b>USB4ACGY</b>	<b>USB4CGY</b>
	Ivory	<b>USB4I</b>	<b>USB4ACI</b>	<b>USB4CI</b>
	Light Almond	<b>USB4LA</b>	<b>USB4ACLA</b>	<b>USB4CLA</b>
White	<b>USB4W</b>	<b>USB4ACW</b>	<b>USB4CW</b>	



**USB20ACPDW**



**USB4ACW**


### Switch Combo Outlets

Description	Color	Catalog Number
Switch Combo Outlet, two USB type 2.0 ports, 2.1 Amp, 5 Volt DC, Style Line® decorator	Black	<b>USB102BK</b>
	Brown	<b>USB102</b>
	Gray	<b>USB102GY</b>
	Ivory	<b>USB102I</b>
	Light Almond	<b>USB102LA</b>
	White	<b>USB102W</b>



### Weather Resistant USB Charger Duplex Receptacles

Description	Color	15A 125V	20A 125V
Type A&C USB Charger Receptacle, One Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant USB ports rated 10,000 cycles; Commercial Grade	Black	<b>USB15AC5BKWR</b>	<b>USB20AC5BKWR</b>
	Brown	<b>USB15AC5WR</b>	<b>USB20AC5WR</b>
	Gray	<b>USB15AC5GYWR</b>	<b>USB20AC5GYWR</b>
	Ivory	<b>USB15AC5IWR</b>	<b>USB20AC5IWR</b>
	Light Almond	<b>USB15AC5LAWR</b>	<b>USB20AC5LAWR</b>
	White	<b>USB15AC5WWR</b>	<b>USB20AC5WWR</b>



Note: Outdoor circuits should be GFCI protected per national and local electric codes.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).