

T5633-GY

Combination Duplex Receptacle/Outlet and USB Charger. 15 Amp, 125 Volt, Decora Tamper Resistant Receptacle/Outlet, NEMA 5-15R. 5.1 Amps, 5VDC, 2.0 Type A and Type-C USB Chargers. Grounding, Side Wired & Back Wired - Gray

The Type A and Type-C™ USB Charger/Tamper Resistant Receptacle offers superior charging power for smartphones, tablets, laptops, monitors, printers and more. Two high powered vertical USB Ports, one Type A and one Type-C, deliver a combined total of 5.1A charging current and 25+ watts of power. Smart chip technology recognizes and optimizes the charging requirements of individual devices and the Type-C port enables the cables to be inserted easily in either direction.



UPC Code: 07847784123

Country Of Origin: China

Technical Information

Electrical Specifications

Amperage: 15 A

Grounding: Grounding

Horsepower Rating: 15A-1/2 HP

Ratings: 15A-125V

Receptacle Voltage: 125V AC

Environmental Specifications

Flammability: Rated V-0 per UL 94

Operating Temperature: -10°C to 40°C

Material Specifications

Body Material: Thermoplastic

Color: Gray

Cover Material: Thermoplastic

Strap Material: Steel

Mechanical Specifications

Product ID: Stamped on Strap

Terminal Accom.: 14-12 AWG

Terminal ID: Brass-Hot Black-Hot
White-Neutral Green-Gnd

Termination: Back & Side

Torque Range: 12-14 inch pounds

Product Features

Amperage: 15 A

Color: Gray

Grade: Spec Grade

Standards and Certifications

Listed: cCSAus

NOM: 057

Warranty: 5 Year Limited

Features and Benefits

- Ideal for residential and commercial applications including kitchens, bedrooms, home offices, college dormitories, airport lounges, hospitals, salons and spas, hotels, meeting rooms, cafes, restaurants and more
 - Smart chip technology recognizes and optimizes the charging requirements of individual devices including Apple, Samsung, Nexus, Pixel and more
 - The Type-C Port provides up to 59% faster charging power versus competitors*
 - One Type A Port and one Type-C Port; combined total of 5.1A of charging power
 - Type-C Port can charge maximum 3 Amps @ 5V
 - Type A Port can charge maximum 2.4 Amps @ 5V
 - Tamper Resistant improves child safety – built-in shutter prevents access by most non-rated/foreign objects
 - USB Ports tested to withstand over 10,000 insertions
 - Charges most Type A and Type-C USB powered devices
 - Type-C Port permits the cables to be inserted easily in either direction
 - Charging time may be affected by the charge cord used. Leviton recommends using the cord provided with the device
 - Compatible with Decora® wallplates and Decora Plus™ screwless wallplates
- * Testing performed using Lightning cable on C Port with iPhone 7, iPad Mini 1, iPad Pro 9.7*

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

