

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE

Suitable for emergency lighting applications such as stairways and hallways.

Certain airborne contaminants can diminish the integrity of acrylic and/or polycarbonate.
[Click here for Acrylic-Polycarbonate Compatibility table for suitable uses.](#)

CONSTRUCTION

Injection-molded, flame-retardant, high-impact, thermoplastic housing with snap-fit design components with LED lamps for easy installation. Universal J-box pattern (j-box not included). Track and swivel arrangement permits full range of lamp adjustment.

OPTICS

The typical life of the LED is 10 years. Two 1W LED lamps for emergency light.

Optional high-output battery to power both local and optional LED remote lamp heads simultaneously. The HO option provides additional 3W of LED remote capacity (up to 2 LED remote heads).

ELECTRICAL

Dual voltage input 120V or 277V AC, 60hz. Emergency unit provided with test switch, status indicator and rechargeable battery. Maintenance-free nickel-cadmium battery provides 90 minutes of emergency power.

INSTALLATION

Wall mount only (not suitable for ceiling mount).

LISTINGS

UL Listed. Meets UL 924, NFPA 101 (current Life Safety Code), NFPA 70-NEC, California Energy Commission Title 20 section 1605.3 (W)(4), FCC Title 47, Part 15, Subpart B and OSHA illumination standards. Indoor damp location 50°F to 104°F (10°C to 40°C) listed standard.

WARRANTY

2-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/support/customer-support/terms-and-conditions

All life safety equipment, including emergency lighting for path of egress must be maintained, serviced, and tested in accordance with all National Fire Protection Association (NFPA) and local codes. Failure to perform the required maintenance, service, or testing could jeopardize the safety of occupants and will void all warranties.

NOTE: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.


Specifications subject to change without notice.

† Small Battery Chargers Certified in the CA Title 20 Appliance Efficiency Database.

Lithonia Lighting Basics™ LED Emergency Light

EU2C

LED Lamps



Weight (shipping): 1.7 lbs. (0.77 kgs.)

All dimensions are inches (centimeters) unless otherwise indicated.

Looking for Contractor Select readily available configurations? Click here to visit Contractor Select™ spec sheet or go to www.contractorselect.com

ORDERING INFORMATION For shortest lead times, configure product using **bolded options**.

Example: EU2C

Series	Housing Color	Options
EU2C Emergency Light	(Blank) Ivory white B Black	(Blank) Not Required HO High Output ¹ SD Self Diagnostics ²

Notes:

- HO not available with SD option.
- SD not available with HO (High Output).

Accessories: Order as separate items.	
ELA WG1	Wireguard (back mount only) ¹
ERE W SGL SQ M12	Single, LED indoor remote head, square, ivory white, 0.75W, 3.6V-12V voltage sensing ^{2,3}
ERE W T SQ M12	Twin LED indoor remote head, square, ivory white, 1.5W, 3.6V-12V voltage sensing ^{2,3}
ERE GY SGL WP SQ M12	Single, LED outdoor remote head, square, gray 1W, 3.6V-12V voltage sensing ^{2,3}
ERE GY T WP SQ M12	Twin LED indoor remote head, square, gray 2W, 3.6V-12V voltage sensing ^{2,3}

Accessories Notes:

- See spec sheet [ELA-WG](#).
- Available with HO option only.
- See spec sheet [ERE](#) remote head.

Description	Supply Voltage	Input Wattage		Input Amps	
		120	277	120	277
Standard (No Options)	120/277	.56	.70	.072	.072
High Output Option (HO)	120/277	.81	1	.12	.12
Self Diagnostic Option (SD)	120/277	.06	.75	.09	.09

Battery	Remote Capacity*	Maximum# Remote Lamp Heads*
3.6V	3W	2 - ERE W SGL SQ M24
		1 - ERE W T SQ M24
		2 - ERE GY SGL WP SQ M12
		1 - ERE GY T WP SQ M12

* These are in addition to the lamp heads on the product

SPACING GUIDELINES

*Note: To see complete photometric report or download the .ies file for this product, visit Lithonia Lighting EU2C home page.

Maximum Spacing Guidelines — EU2C ¹						
Mounting Height	Illumination Level	Single Luminaire		Multiple Luminaires		Application Notes
		3' Path of Egress	6' Path of Egress	3' Path of Egress	6' Path of Egress	
7.5'	1FC Avg	10'	6'	14'	11'	100' Corridor 8' wide, and 9' high with 80/50/20 reflectances

Notes:

1. Also meets the additional illumination requirements of NFPA 101: 1FC minimum and max/min ratio of 40:1.

