

# VT SERIES RELIGHT



## REALIZE YOUR BUILDING'S POTENTIAL WITH RELIGHT ASSEMBLY KITS

VT SERIES RELIGHT kits will enhance your environment and save more energy.  
[www.lithonia.com/RELIGHT](http://www.lithonia.com/RELIGHT)





# IMPROVE YOUR LIGHTING WITH VT SERIES RELIGHT



installs in existing housing

true volumetric lighting

advanced LED technology

## ENHANCE YOUR SPACE

- VTLED relight assembly kits bring a modern refreshing look to your ceiling and your space
- Contemporary aesthetics and improved proportions create a quiet ceiling
- Easy one-to-one fixture upgrades help you realize your building's potential with the latest LED technology

## UPGRADE YOUR LIGHTING QUALITY


- Offers more balanced luminous lighting, eliminating shadowy cave effects created by parabolics
- Controls high-angle brightness, reducing glare for computer monitors and occupants
- Available in both 2'x4' and 2'x2' LED and fluorescent configurations

## EFFICIENT AND ENVIRONMENTALLY FRIENDLY

- Energy consumption is lowered with advanced LEDs for more efficient lighting
- Long lasting LEDs result in reduced maintenance and disposal costs

## QUICK AND EASY INSTALLATION

- Assembly kits are designed for quick installation without the need to access above the ceiling plane



### ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: 2VTL2R 33L D37 LP835 NX

VTLR						
Series		Lamp type	Voltage	Driver	Lamp	Control
2VTL2R	Recessed 2X2 relight assembly (black end bracket flanges for parabolic installation)	33L	(blank) MVOLT (120-277V)	D37 37 watt	LP835 82CRI,3500K	NX dimming driver, no nLIGHT controls
2VTL4R	Recessed 2X4 relight assembly (black end bracket flanges for parabolic installation)	45L	(blank) MVOLT (120-277V)	D49 49watt	LP835 82CRI,3500K	NX dimming driver, no nLIGHT controls
VTLRT						
Series		Lamp type	Voltage	Driver	Lamp	Control
2VTL2RT	Recessed 2X2 relight assembly (white end bracket flanges and trim kit for lensed troffers)	33L	(blank) MVOLT (120-277V)	D37 37 watt	LP835 82CRI,3500K	NX dimming driver, no nLIGHT controls
2VTL4RT	Recessed 2X4 relight assembly (white end bracket flanges and trim kit for lensed troffers)	45L	(blank) MVOLT (120-277V)	D49 49 watt	LP835 82CRI,3500K	NX dimming driver, no nLIGHT controls

