

Project Name

Location

Prepared By



SATCO S29929

12T8/LED/36-850/BP 120-277V

Notes

[www] 10-11-2021 02:00:31

General

Status	Discontinued
Substitute	S39929
Watts	12W
Fluorescent Equivalent	25W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	36
Finish	Frost
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	82
Lumens	1450L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	36
MOD	1
Lens Finish	Frost

Additional Information

Additional Info	All glass tube
Tube Guard Use	Approved for use with tube guards
Installation Notes	Existing wiring to both sockets can remain in place. Will work on both shunted or non-shunted sockets.
Specification Note	Built-in shock resistant circuit - (not hot until both ends are installed)
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLCM6AAFCP4G
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes

