NUDTW-88 Series

LEDUR Tunable White 120V Edge-Lit Under Cabinet

LEDUR LED Tunable White under cabinet uses edge-lit

placement of diodes to give a Uniform Reflectance of

switch. The LEDUR TW produces an even 475 lumens / 7 watts average per foot. Dimmable, no UV and forward

heat make LEDUR TW the perfect energy saving lighting

solution in under cabinet and shelf lighting. The LEDUR TW's

uniform reflectance is excellent when used under cabinet

over granite, polished stone or any reflective surface,

additionally it is excellent in retail display lighting where

diode image might distract from display merchandise.

light. The LEDUR TW allows the end user to select between

kelvin temperatures at time of installation with a 3 position

Source: 7W

PRODUCT DESCRIPTION

475lm per foot

ELECTRICAL

Input Voltage: 120V Lumens: 475lm per foot

Wattage:

8" = 4.9W; **11"** = 6.7W; **18"** = 11W; **22"** = 12W; **32"** = 16W; **42"** = 16W

Color Temperature:

(blank) = 2700K / 3000K / 3500K /345 = 3000K / 4000K / 5000K Color Rendering Index: 90+CRI

Operating Temp.: 0°C to 45°C ambient temperature

Maximum Run Length: 400W Dimming: Triac or ELV

Click Here or check complete dimmer list at www. NoraLighting.com in the "Compatibility" page under

"Resources" tab.

FEATURES

Two luminaires available in three kelvin temperatures each

(One luminaire offers 2700K / 3000K / 3500K, another is offered in 3000K / 4000K / 5000K)

- · Edge lit design eliminates LED diode image
- · Excellent color rendition 90+ CRI
- 475 Lumens/ 7 watts per foot average
- · Available in 6 different lengths
- · Dark Bronze or White Finish
- Built-in on/off rocker switch and 3 position sliding color temperature switch
- · Linkable up to 400 Watts fixtures
- 3 wire grounded electrical port on both ends for power or linking
- · Quick connect stab-in connectors included
- Captive Screws for easy moutning
- · Integral electronic dimmable driver

Included with every fixture: Mounting Hardware and V_z''' die-cast metallic cable clamp, end to end connector, installed On/Off rocker switch and 3 position kelvin selection switch.

CONSTRUCTION

Housing: Rear wireway access cover with stab-in electrical connectors facilitate wiring without opening the fixture. Additional knock-outs for top and back wiring.

Installation: Mounting hardware is included with each unit. Captive screws allow for quick installation, simply wire using rear door and quick connects, and hold in place and drive captive screws into material. Captives screws are covered with an included cap for a beautiful finished look.

LABELS AND LISTINGS

- · cULus Listed for Dry Location
- ENERGY STAR® Certified
- · 5-Year Limited Warranty
- Certified to the high efficacy requirements of California Title 24 JA8-2019










PRODUCT IMAGES AND DIMENSIONS

Type


Project

Notes

Catalog No.



Captive Screws for easy mounting located at each end under removable cap



LEDUR Tunable White 120V Edge-Lit Under Cabinet

NUDTW-8808/BZ = 8" Bronze (2700K / 3000K / 3500K) NUDTW-8808/WH = 8" White (2700K / 3000K / 3500K) NUDTW-8811/BZ = 11" Bronze (2700K / 3000K / 3500K) NUDTW-8811/WH = 11" White (2700K / 3000K / 3500K) NUDTW-8818/BZ = 18" Bronze (2700K / 3000K / 3500K)

NUDTW-8818/WH = 18" White (2700K / 3000K / 3500K) (Discontinued, direct replacement: NUDTW-8818/23345WH)

NUDTW-8822/BZ = 22" Bronze (2700K / 3000K / 3500K)

NUDTW-8822/WH = 22" White (2700K / 3000K / 3500K) (Discontinued, direct replacement: NUDTW-8822/23345WH)

NUDTW-8832/BZ = 32" Bronze (2700K / 3000K / 3500K)

NUDTW-8832/WH = 32" White (2700K / 3000K / 3500K) (Discontinued, direct replacement: NUDTW-8832/23345WH)

NUDTW-8842/BZ = 42" Bronze (2700K / 3000K / 3500K)

NUDTW-8842/WH = 42" White (2700K / 3000K / 3500K) (Discontinued, direct replacement: NUDTW-8842/23345WH)

NUDTW-8808/345BZ = 8" Bronze (3000K / 4000K / 5000K) NUDTW-8808/345WH = 8" White (3000K / 4000K / 5000K) NUDTW-8811/345BZ = 11" Bronze (3000K / 4000K / 5000K)

NUDTW-8811/345WH = 11* White (3000K / 4000K / 5000K) (Discontinued, direct replacement: NUDTW-8811/23345WH)
NUDTW-8818/345BZ = 18* Bronze (3000K / 4000K / 5000K) (Discontinued, direct replacement: NUDTW-8818/23345BZ)
NUDTW-8818/345WH = 18* White (3000K / 4000K / 5000K) (Discontinued, direct replacement: NUDTW-8818/23345WH)

NUDTW-8822/345BZ = 22" Bronze (3000K / 4000K / 5000K)

NUDTW-8822/345WH = 22* White (3000K / 4000K / 5000K) (Discontinued, direct replacement: NUDTW-8822/23345WH)
NUDTW-8832/345BZ = 32* Dronze (3000K / 4000K / 5000K) (Discontinued, direct replacement: NUDTW-8832/23345BZ)
NUDTW-8832/345WH = 32* White (3000K / 4000K / 5000K) (Discontinued, direct replacement: NUDTW-8832/23345WH)

NUDTW-8842/345BZ = 42" Bronze (3000K / 4000K / 5000K) **NUDTW-8842/345WH** = 42" White (3000K / 4000K / 5000K)

Example: NUDTW-8822/WH = 22" LEDUR Tunable White 120V Edge-Lit Under Cabinet, Selectable CCT (2700K / 3000K / 3500K) White Finish



NUDTW-88 Accessories

LEDUR Tunable White 120V Edge-Lit Under Cabinet

Source: 7W

350lm per foot

Type
Project
Catalog No.
Notes





NUA-802B Black
NUA-802W White
Used to power NUDTW-88 series using
Jumper Cables or NUA-804 Hardwire
Connector.
Finish: Black or White



End to End Connector

NUA-803 Used to join two NUDTW-88 fixtures seamlessly together. 3-wire grounded connector. Finish: White



72" 3-Wire Grounded Hardwire Connector

NUA-804B Black
NUA-804W White
Used to hardwire NUDTW-88 fixtures to
NUA-802 or junction box (by others).
Finish: Black or White



72" Cord & Plug

NUA-805B Black NUA-805W White Convert NUDTW-88 series fixtures from hardwire to direct plug-in units. Finish: Black or White



Jumper Cable

NUA-806B 6" Black NUA-806W 6" White NUA-812B 12" Black NUA-812W 12" White NUA-824B 24" Black NUA-824W 24" White NUA-872B 72" Black NUA-872W 72" White

Used to join NUDTW-88 fixtures together or to NUA-802. Finish: Black or White

