

## Specification Sheet

Part Number: 151-01630


For use with HellermannTyton T18 - T30 cable ties to provide stability when securing bundles.

4-way opening allows cable ties to be installed parallel or perpendicular to bundles.

The high-heat, high-bond adhesive is ideal for outdoor applications, with a static load weight of 0.6 lb.

Two predrilled holes extend mounting options and solutions.

Extended adhesive liner is easy to remove quickly.



High Heat High Bond Acrylic Adhesive Base, 0.75 x 0.75", Use T18-T30 Tie, PA66HIRHSUV, Black, 500/pkg

Article Number 151-01630

Type MB3A4

Color Black (BK)

Quantity Per bag

Product Description MB3A4 adhesive mounts are for use with HellermannTyton T18 - T30 Series cable ties to provide stability when securing bundles. The high-heat, high-bond acrylic adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options.

|                                     |   |
|-------------------------------------|---|
| Short Description                   | High Heat High Bond Acrylic Adhesive Base, 0.75 x 0.75", Use T18-T30 Tie, PA66HIRHSUV, Black, 500/pkg |
| Global Part Name                    | MB3A4-PA66HIRHSUV-BK  |
| Length L (Imperial)                 | 0.75  |
| Length L (Metric)                   | 19.0  |
| Fixation Method                     | Adhesive  |
| Width W (Imperial)                  | 0.75  |
| Width W (Metric)                    | 19.0  |
| Cable Ties                          | T18 - T30   |
| Height H (Imperial)                 | .19   |
| Height H (Metric)                   | 4.8   |
| Cable Tie Width Max (Imperial)      | 0.14  |
| Cable Tie Width Max (Metric)        | 3.6   |
| Mounting Hole Diameter D (Imperial) | 0.12  |
| Mounting Hole Diameter D (Metric)   | 3.0 mm  |
| Mounting Hole Centers (Imperial)    | 0.52  |

|                                |  |
|--------------------------------|--|
| Material                       | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut              | PA66HIRHSUV  |
| Adhesive                       | Acrylic foam   |
| Flammability                   | UL 94 HB (excluding adhesive)  |
| UV Resistant (Yes/No)          | Yes  |
| Use Conditions                 | For Indoor and Outdoor Use   |
| Adhesive Operating Temperature | -40°F to +176°F (-40°C to +80°C)   |
| Operating Temperature          | -40°F to +221°F (-40°C to +105°C)  |
| Reach Compliant (Article 33)   | No   |
| ROHS Compliant                 | Yes  |
| Package Quantity (Imperial)    | 500  |
| Package Quantity (Metric)      | 500  |
| Customs Number                 | 3926909988   |

