

USB Charger Receptacles and Outlets

Wireless Chargers

Description	Color	Rating	Receptacle	Catalog Number
Wireless wall mount phone charger	White	Coil: 7.5 watt inductive, 125V AC input	-	USB1518



Combination Wireless Chargers

Description	Color	Rating	Receptacle	Catalog Number
Combination wireless wall mount phone charger, inductive coil with USB Type A&C ports, and tamper-resistant receptacle	White	Coil: 7.5 watt inductive, USB: 5A 5V DC Input: 125V AC	15A 125V 20A 125V	USB1528AC USB2028AC



Standard USB Charger Tamper-Resistant Duplex Receptacles

Description	Color	15A 125V	20A 125V
Type-C USB Charger Receptacle, two Type-C port configurations, high power 5 Amp, 5 Volt USB output.	Black	USB15C5BK	USB20C5BK
	Brown	USB15C5	USB20C5
	Gray	USB15C5GY	USB20C5GY
	Ivory	USB15C5I	USB20C5I
	Light Almond	USB15C5LA	USB20C5LA
Type A&C USB Charger Receptacle, one Type A and one Type-C port configuration, high power 5 Amp, 5 Volt USB output.	Black	USB15AC5BK	USB20AC5BK
	Brown	USB15AC5	USB20AC5
	Gray	USB15AC5GY	USB20AC5GY
	Ivory	USB15AC5I	USB20AC5I
	Light Almond	USB15AC5LA	USB20AC5LA
Type A USB Charger Receptacle, two Type A port configurations, high power 5 Amp, 5 Volt USB output.	Black	USB15A5BK	USB20A5BK
	Brown	USB15A5	USB20A5
	Gray	USB15A5GY	USB20A5GY
	Ivory	USB15A5I	USB20A5I
	Light Almond	USB15A5LA	USB20A5LA
White	USB15A5W	USB20A5W	



USB1528AC



USB15C5W



USB15AC5W



USB20A5W

Note: See page Tech-10 for Tamper-Resistant description.
See section L for Hospital grade series.



4 Port USB Charger Outlets

Description	Color	4 Type A ports	2 Type A and 2 Type-C ports	4 Type-C ports
USB Charger Outlets, 4 USB ports, 5 Amp, 5 Volt DC, Style Line® decorator.	Black	USB4BK	USB4ACBK	USB4CBK
	Brown	USB4	USB4AC	USB4C
	Gray	USB4GY	USB4ACGY	USB4CGY
	Ivory	USB4I	USB4ACI	USB4CI
	Light Almond	USB4LA	USB4ACLA	USB4CLA
	White	USB4W	USB4ACW	USB4CW



Switch Combo Outlets

Description	Color	Catalog Number
Switch Combo Outlet, two USB type 2.0 ports, 2.1 Amp, 5 Volt DC, Style Line® decorator	Black	USB102BK
	Brown	USB102
	Gray	USB102GY
	Ivory	USB102I
	Light Almond	USB102LA
	White	USB102W



Weather Resistant USB Charger Duplex Receptacles

Description	Color	15A 125V	20A 125V
Type A&C USB Charger Receptacle, One Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant USB ports rated 10,000 cycles; Commercial Grade	Black	USB15AC5BKWR	USB20AC5BKWR
	Brown	USB15AC5WR	USB20AC5WR
	Gray	USB15AC5GYWR	USB20AC5GYWR
	Ivory	USB15AC5IWR	USB20AC5IWR
	Light Almond	USB15AC5LAWR	USB20AC5LAWR
	White	USB15AC5WWR	USB20AC5WWR



Note: Outdoor circuits should be GFCI protected per national and local electric codes.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).