SATCO NUVO

Project Name

Location

Prepared By



N	o	te	S

[www] 11-22-2021 02:57:4

Compliance

General	
Status	Active
Watts	45W
Incandescent Equivalent	300W
Fluorescent Equivalent	65W
HID Equivalent	175W
Volts	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	80
Lumens	6435L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 11 in. Width: 8 in. Depth: 8 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 100-277V
Working Voltage Operating Frequency	AC 100-277V 50/60 Hz
Operating Frequency	50/60 Hz
Operating Frequency Power Factor	50/60 Hz >0.9
Operating Frequency Power Factor Burning Position	50/60 Hz >0.9 Universal
Operating Frequency Power Factor Burning Position Surge Protection	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34 Plastic (PS)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34 Plastic (PS) Plastic (PS)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34 Plastic (PS) Plastic (PS) White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34 Plastic (PS) Plastic (PS)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34 Plastic (PS) Plastic (PS) White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34 Plastic (PS) Plastic (PS) White
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34 Plastic (PS) Plastic (PS) White 1.81 Approved for totally enclosed fixtures; Base up, base down or horizontal operation; For outdoor & indoor use; Emits no UV light /
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34 Plastic (PS) Plastic (PS) White 1.81 Approved for totally enclosed fixtures; Base up, base down or horizontal operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)
Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	50/60 Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to a maximum of +45C (+113F) 8.5 3.34 Plastic (PS) Plastic (PS) White 1.81 Approved for totally enclosed fixtures; Base up, base down or horizontal operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes

Safety Listing	cULus	
Location Rating	Damp	
Energy Star	No	
California Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
SDS Sheet	LED Lamp	

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







