


VT-TNR414P(2)

4 Channel 8 MegaPixel H.265 Real Time Network Video Recorder with 4K Output & 4 Port PoE Switch



Transcend Series Network Video Solutions combine the simplicity of Stand Alone, Plug and Play Recorders and surveillance cameras with professional features and versatile design options. Available in 4, 8, 32, and 64 channel configurations, these simple to use and easy to install NVRs support High Definition IP security cameras up to 8 Megapixel. A perfect pairing with Transcend IP Cameras for quick, professional installation offering a variety of viewing options such as Central Monitoring (CMS) and Internet Explorer along with simple yet intuitive IOS and Android apps. Both the Transcend High Definition Analog and Network recorders share the same client, CMS viewing platform and Mobile apps. Camera options include fixed, varifocal and vandal / weather resistant models.

FEATURES

- 4 Channel Stand-alone Real-time IP Network Video Recorder
- Full 8 Megapixel (4K) Real-time recording (120fps) with 120fps playback
- 4K HDMI & VGA Video Outputs
- H.265 / H.264 Video Compression
- Plug and Play & Auto configuration for many leading ONVIF compliant IP Camera models
- Internal 4-Port PoE Switch
- 1 Gigabit LAN Port
- Pentaplex: Live Display / Record / Playback / Backup / Remote Access
- 1 Internal SATA2/SATA3 HDD Slot supporting up to 10TB (1 x 10TB HDD) Internal Storage
- Network Based PTZ Control
- Applications for iOS® & Android®
- Remote Viewing over the Internet via Web Browser or LAN
- Mac OS® Client & CMS Central Management Software Included
- Supports both Dynamic and Static IP Addresses
- Web-based remote configuration
- Control locally via USB Mouse or with the Included IR Remote control



Local Management, Viewing Interface & Remote Viewing with Web Browsers



Remote Viewing Using Mac OS X



Apps Available for iPhone, iPad, & Android Devices



Rear Connections



(888) VITEK-70 | WWW.VITEKCCCTV.COM
28492 Constellation Road Valencia, CA 91355

An Eye On
Innovation

VT-TNR414P(2)

4 Channel 8 MegaPixel H.265 Real Time Network Video Recorder with 4K Output & 4 Port PoE Switch

VT-TNR414P Specifications

| | |
|--------------------------|--|
| Video Input / Resolution | 4 IP Channels up to 8 MegaPixel |
| Main Monitor Output | 1 x 4K HDMI / 1 x 1080P VGA |
| Multi Operation | Pentaplex: Live Display / Record / Playback / Backup / Remote Access |
| Recording Compression | H.265 / H.264 |
| OS | Embedded Linux |
| Recording | 120fps (30fps per channel) |
| Audio over IP Inputs | 4 (1 Audio Channel per IP Camera over IP) |
| Local Audio In/Out | IN: RCA x 1CH / OUT: RCA x 1CH |
| Two-Way Audio | YES |
| Encode | CBR |
| Quality Levels | 11 level (According to Bit Rate) |
| Recording Modes | Manual / Timer / Motion / Sensor |
| File Management | Reserving time, Redundancy, Dual stream recording |
| Local Playback | 4CH |
| Search | Time sliced image search, Time/Calendar search, Event (Motion, External alarm), Tag search |
| Alarm Modes | Sensor, Motion, Video loss, IP conflict, Disk error, Illegal access, Network disconnection |
| Alarm Inputs | IP Camera Dependent (No Local Input) |
| Alarm Triggering | Record, Snap, PTZ move, Alarm out, E-mail, etc |
| Network Interface | RJ45 x 1 |
| POE ports | RJ45 x 4, with POE |
| PoE Standard | 802.3af 15W max per port |
| Total PoE Budget | 50W all ports |
| Bit Rate (Per Camera) | 512Kbps ~ 10 Mbps (Adjustable) |
| Total Bandwidth | 50Mbps Incoming / 50Mbps Outgoing |
| Dual-stream | Individual Network Video Stream and local recording stream, set separately |
| Network Protocols | TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS, Email, UPNP, NAT, Telnet |
| Internet-streaming | Total 28 task resource (Local+Remote) 4 CH IE playback |
| Remote Viewing | CMS / Web Browser / Mobile Platforms |
| Remote Users | 10 Simultaneous Online Users |
| Backup | Network, USB |
| SATA HDD | SATA x 1, max to 10TB each |
| PTZ Protocol | Through Network |
| USB | USB 2.0 x 2 (for mouse and USB backup device) |
| Power Consumption | ≤ 5W (Without HDD) |
| Power Supply | 48V/2.5A |
| Working Environment | 32° ~ 122°F @ 10% ~ 90% RH |
| Weight | 4.41lbs (2kg) |
| Dimensions (WxHxD) | 10.43" x 1.77" x 8.07" (265mm×45mm×205mm) |

