

Eaton DH225FRK

Catalog Number: DH225FRK

Eaton Heavy duty single-throw fused safety switch, Enhanced visible blade, 400 A, NEMA 3R, Two-pole, Two-wire, 240 V, Max Hp: 50, 125, 50 hp (3PH @ Std fuse/time delay/250 Vdc), (2)#1/0-(2)300 kcmil or (1)#1/0-(1)750 kcmil Al



Photo is representative

General specifications

Product Name	Catalog Number
Eaton heavy duty fusible safety switch	DH225FRK
UPC	Product Length/Depth
782114001981	7.27 in
Product Height	Product Width
44.74 in	23.08 in
Product Weight	Warranty
120 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
NEC 230.62 (C) Compliant Barrier	UL Listed

Catalog Notes

Suitable for service entrance use with a neutral or ground lug kit installed. Hp ratings apply only when neutral is field installed and switch is used on a grounded B phase system.

Physical Attributes

Enclosure

NEMA 3R

Enclosure material

Painted galvanized steel

Fuse class provision

Class H

Fuse configuration

Fusible without neutral

Number Of Poles

Two-pole

Number of wires

2

Type

Heavy duty fusible safety switch

Performance Ratings

Amperage Rating

400A

HP rating - max

50, 125, 50 hp (3PH @ Std fuse/time delay/250 Vdc)

NEMA rating

NEMA 3R

Voltage rating

240V

Miscellaneous

Product Category

Heavy Duty, Fusible without neutral

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Specifications and datasheets

[Eaton Specification Sheet - DH225FRK](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia