

Project Name

Location

Prepared By



SATCO S11924

14T8/LED/48-865/BP 120-277V

Notes

[www] 06-09-2021 01:41:21

General

Status	Discontinued
Substitute	S21924
Watts	14W
Fluorescent Equivalent	25W-32W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	6500
Temperature	Daylight
CRI	82
Lumens	1800L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	48
MOD	1
Lens Finish	Frost

Additional Information

Additional Info	All glass tube; Built-in shock resistant circuit
Tube Guard Use	Approved for use with tube guards
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes