

TS 15X5/LL 2M/ST/ZN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image

Steel DIN rails are the most widespread on the market. Among metal DIN rails, they have the lowest shortcircuit protection, similar to stainless steel.

General ordering data

Version	Rail, TS 15, with slot, Steel, galvanic zinc plated and passivated
Order No.	0117500000
Type	TS 15X5/LL 2M/ST/ZN
GTIN (EAN)	4008 190150662
Qty.	2 m

Creation date December 29, 2021 8:50:01 PM CET

Catalogue status 17.12.2021 / We reserve the right to make technical changes.

TS 15X5/LL 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	5.5 mm	Depth (inches)	0.217 inch
Height	15 mm	Height (inches)	0.591 inch
Width	2,000 mm	Width (inches)	78.74 inch
Net weight	140 g		

Mounting rail

Drill-hole diameter	4.2 mm	
Installation advice	Direct mounting	
Length of the terminal rail	max.	2,000 mm
	nominal	2,000 mm
	min.	0 mm
Material	Steel	
Pre-punched mounting rail	Yes	
Short circuit strength corresponds to E-Cu wire	10 mm ²	
Short-time withstand current according to IEC 60947-7-2	1.2 kA/1s	
Slit gap	8 mm	
Slit gap		
Slit length	12 mm	
Slit length		
Slit width	4.2 mm	
Slit width		
Slotted drill holes	Yes	
Solder eyelet hole diameter (D)	4.2 mm	
Spacing of holes, centre-to-centre	20 mm	
Standards	DIN EN 60715	
Surface finish	galvanic zinc plated and passivated	
Thickness	1 mm	

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ETIM 8.0	EC001285	ECLASS 9.0	27-40-06-02
ECLASS 9.1	27-40-06-02	ECLASS 10.0	27-40-06-02
ECLASS 11.0	27-40-06-02		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	