



LightGuard® 350-AC Drop Access Sealed Fiber Optic Splice Closure

The LightGuard (LG) 350-AC is a sealed dome closure designed for medium count fiber splicing (up to 144 single or 432 mass) in a butt configuration where space may be limited. Utilized in aerial or underground environments where a sealed closure is required, the LG-350-AC is designed for “drop access” applications providing access for up to 12 drops. The LG-350-AC is ideal for for Fiber-to-the-Home installations in small hand-hole application and requires only a common can wrench for installation.

Features

- Less than 20" overall length; ideal for small hand-holes
- Supports stranded loose tube or ribbon fiber cables in either armored or dielectric configurations
- Installation and re-entry requires only a common can wrench
- Fully sealed to protect fiber and splices ensuring longevity
- Fully kitted with all parts to install two cables and up to 12 drops

Specifications

| PARAMETER | VALUE | |
|------------------------------------------------------------|-----------------------------------|------------------------|
| Splice Capacity (Max.)—Single, Mass, Mechanical | 144, 432, 48 | |
| Number of Splice Trays (Max.) - Single , Mass, Mechanical* | 4, 3, 4 | |
| Cable Entrance Configuration | Butt | |
| Cables | 2 to 8 Express with up to 12 Drop | |
| Cable Sizes (Min. O.D. - Max. O.D.) | (2) Express Ports | (3) Drop Ports |
| Included Grommets | 0.40" - 1.00" | (4 port) 0.26" - 0.80" |
| Single in. (mm) | (10.0 - 25.4) | |
| (4) Flat Drop Only in. (mm) | | (6.6 - 20.0) |
| Additional Grommets | | |
| Dual Express Port Only in. (mm) | 0.26" - 0.44" | |
| | (6.6 - 11.2) | |
| Quad Express Port Only in. (mm) | 0.26" - 0.38" | |
| | (6.6 - 9.7) | |
| (4) Flat Drop Port Only in. (mm) | | 0.19" x 0.34" |
| | | (4.8 x 8.6) or |
| | | 0.25" round (6.4) |
| Dimensions - (L x D) in. (mm) | 19.8" x 10.0" (503.0 x 254.0) | |
| Weight - lbs. (kg) | 12.0 (5.44) | |

continued
→

LightGuard® 350-AC Drop Access Sealed Fiber Optic Splice Closure

Ordering Information

| DESCRIPTION | AFL NO. |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| LG-350-AC Fiber Optic Splice Closure—Stores 144 single fusion or 432 mass fusion, includes (2) Express cable kits and (12) Drop cable kits for sealing/retention and (2) ground terminals with removable bond. Included: (1) LL-4808L Splice Tray Not included: Cable Grounding Kits, or Hanger Brackets | FC000412 |
| LL-4808L-R Universal Splice Tray—Stores (36) single fusion splices or (12) mass fusion splices (144 F). Maximum of 4 trays in the LG-350-AC. | FA000037 |
| LL-4808-R Mass Splice Tray—Stores (12) mass fusion splices (144 F). Maximum of 4 trays in the LG-350-AC | FA000020 |
| LL-4808-L Single Splice Tray—Stores (36) single fusion splices. Maximum of 4 trays in the LG-350-AC | FA000021 |
| LG-350 Single Grommet Kit (Min. 0.40" - Max. 1.00")—For use in LG-55/LG-350/LG-350-AC on Express Port side | FC000726 |
| LG-350 Dual Grommet Kit (Min. 0.26" - Max. 0.44")—For use in LG-55/LG-350/LG-350-AC on Express Port side | FC000337 |
| LG-350 Quad Grommet Kit (Min. 0.26" - Max. 0.38")—For use in LG-55/LG-350/LG-350-AC on Express Port side | FC000421 |
| LG-350 Single Grommet Kit (Min. 0.26" - Max. 0.80")—For use in LG-350/AC/SD on Drop Port side | FC000727 |
| LG-350 Drop 4 Flat Drop Grommet Kit—For use with standard flat drop cable and round cable up to 0.25" O.D. | FC000422 |
| Universal Aerial Strand Hanger Kit—For use with LG-150/250/350 | FC000006 |
| Extended Offset Strand Hanger Kit—For use with LG-150/250/350 | FC000208 |
| PWK Pole or Wall Mount Bracket—For use with LG-150/250/350 | LGBR-30 |
| OPGW Dual Cable Bracket Kit—For use with LG-150/250/350 | FC000683 |
| 1x6 Fiber Router Kit with furcation tubes | FC000070 |
| CGK-5 Cable Grounding Kit (pack of 5)—Clamp-On Ground Cable Only | FC001091 |
| *Mechanical Splice Kit. Includes 10 pieces of VHB tape. Used in all splice trays. Each piece holds 12 splices. | FA000089 |
| LG-350 O-Ring and Lock Ring Kit—For use with LG-350/AC/SD | FC000775 |

* See Accessory Specifications.
See Splice Tray Specifications.

Qualifications

| GOVERNING BODY | STANDARD CODE |
|-------------------------------|---------------|
| Telcordia | GR-771 |
| Rural Utilities Service (RUS) | Listed |

Contact AFL for further details.