



## Laser Level with Bubble Vials, Magnetic



The Klein Tools Laser Line Bubble Level LBL100 projects a high power horizontal laser line and spot parallel to the base that reaches up to 75-Foot (22.9 m). Use the laser to align ceiling tiles, floor tile, studs, wood, saws, and more. Three easy to read vials identify horizontal and cross at 0-Degree level and vertical at 90-Degree. The strong Rare-Earth magnets in the base of the level attach to the included leveling stand and other ferromagnetic surfaces. The top features a V-groove to fit the contour of pipe, conduit, beam, pole, and other round surfaces. Includes a leveling stand for manual leveling on uneven surfaces.

### Specifications

<b>Type:</b>	Laser and Bubble	<b>Application:</b>	Layout Applications Requiring Level and Plumb Checks
<b>Special Features:</b>	1/4-20 Threaded Hole for Tripod, Cross Bubble Vial, Leveling Base Included, Magnetic Mounting, V-groove	<b>Material:</b>	Cast Aluminum
<b>Batteries:</b>	3 x AAA	<b>Laser Wavelength:</b>	630 to 670nm
<b>Number of Beams:</b>	1	<b>Laser Color:</b>	Red
<b>Laser Class:</b>	Class 3a	<b>Laser mW:</b>	<5mW
<b>Plumb Laser:</b>	No	<b>Indoor Range:</b>	0 to 75' (0 to 23 m)
<b>Maximum Distance (Feet):</b>	75	<b>Maximum Distance (m):</b>	22.9
<b>Number of Vials:</b>	3	<b>Type of Vials:</b>	0° Horizontal and Cross, 90° Vertical
<b>Accuracy:</b>	Vials: 0.043°; Spot: +/-0.02" (+/-0.5 mm) at 39.4" (1 m) from Level	<b>Pulse Mode:</b>	No
<b>Receiver:</b>	No	<b>Magnet Type:</b>	Neodymium (Rare Earth)
<b>Ingress Protection:</b>	IP54: Dust and Water Resistant	<b>Transit Locking Mechanism:</b>	No
<b>Standard:</b>	IEC60825-1	<b>Included:</b>	Level; Leveling Stand; Batteries
<b>Overall Length (Inch):</b>	7.3	<b>Overall Length (cm):</b>	18.5
<b>Overall Height:</b>	1.84" (4.7 cm)	<b>Overall Width (Inch):</b>	0.85
<b>Overall Width (cm):</b>	2.2	<b>Weight (lb):</b>	0.98
<b>Weight (kg):</b>	0.4	<b>Overall Height (Inch):</b>	1.84
<b>Overall Height (cm):</b>	4.7		