

Eaton LE215CC07TSA2

Catalog Number: LE215CC07TSA2

Eaton Cooper Power series loadbreak elbow, Std V:15kV, Max phase-to-ground:8.3kV, AC 1 min:34kV, DC 15 min:34kV, Impulse:95kV, Max corona:11kV, Test:No, 0.75 inch, 1.08 inch, 2/0 AWG, 3/0 AWG, Cable shield adapter 0.830-1.640" (SA2), 20 pk

General specifications



Product Name	Catalog Number
Eaton Cooper Power series loadbreak elbow	LE215CC07TSA2
	UPC
	194006091671
Product Length/Depth	Product Height
7.6 in	9 in
Product Width	Product Weight
2.9 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE 386

Product specifications

AC 1 minute voltage withstand

34 kV

Cable insulation diameter - min

0.75 in

DC 15 minute withstand

34 kV

Type

Loadbreak elbow

Standard pack

20 pack

Stranded or compressed conductor size

2/0 AWG

Maximum rating phase-to-ground

8.3 kV

Cable sealing kit

Cable shield adapter 0.830"-1.640" (SA2)

Current rating

200 A

Standard voltage class

15 kV

Cable insulation diameter - max

1.08 in

Corona voltage level - min

11 kV

Basic impulse level

95 kV

Solid or compact conductor size

3/0 AWG

Resources

Application notes

[Line installation and protective equipment product application poster](#)

Catalogs

[Line installation and protective equipment Flex Center product aid](#)

Cross references

[loadbreak-elbow-connector-idea-cross-reference](#)

Specifications and datasheets

[Eaton Specification Sheet - LE215CC07TSA2](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)