

15 and 20 Ampere, 125 and 250 Volts



15A 125V
NEMA 5-15R
UL CSA
0.5 HP




20A 125V
NEMA 5-20R
UL CSA
1 HP




SNAPConnect Extra Heavy Duty Receptacles

Style Line® Decorator	Color	Catalog Number	
Specification grade, Style Line decorator, flush, nylon face, modular receptacle which requires pigtailed connector below.	Black Brown Gray Ivory Light Almond Red White	SNAP2152BKA SNAP2152A SNAP2152GYA SNAP2152IA SNAP2152LAA SNAP2152RA SNAP2152WA	SNAP2162BKA SNAP2162A SNAP2162GYA SNAP2162IA SNAP2162LAA SNAP2162RA SNAP2162WA
Specification grade, Tamper-Resistant, Style Line decorator, flush, nylon face, modular receptacle which requires pigtailed connector below.	Black Blue Brown Gray Ivory Light Almond Red White	SNAP2152BKTRA SNAP2152BLTRA SNAP2152TRA SNAP2152GYTRA SNAP2152ITRA SNAP2152LATRA SNAP2152RTRA SNAP2152WTRA	SNAP2162BKTRA SNAP2162BLTRA SNAP2162TRA SNAP2162GYTRA SNAP2162ITRA SNAP2162LATRA SNAP2162RTRA SNAP2162WTRA
Specification grade, Tamper-Resistant, Split Circuit, Style Line decorator, flush, nylon face, modular receptacle which requires pigtailed connector below.	Black Blue Brown Gray Ivory Light Almond Red White	SNAP2152BKSCTRA SNAP2152BLSCTRA SNAP2152SCTRA SNAP2152GYSCTRA SNAP2152ISCTRA SNAP2152LASCTRA SNAP2152RSCTRA SNAP2152WSCTRA	SNAP2162BKSCTRA SNAP2162BLSCTRA SNAP2162SCTRA SNAP2162GYSCTRA SNAP2162ISCTRA SNAP2162LASCTRA SNAP2162RSCTRA SNAP2162WSCTRA
Isolated ground ^A , Specification grade, TR.	Orange	SNAP2152IGTRA	SNAP2162IGTRA
Specification grade, with Power Indicating LED, Style Line decorator, flush, nylon face, modular receptacle which requires pigtailed connector below.	Black Blue Brown Gray Ivory Light Almond Red White	SNAP2152BKL SNAP2152BLL SNAP2152L SNAP2152GYL SNAP2152IL SNAP2152LAL SNAP2152RL SNAP2152WL	SNAP2162BKL SNAP2162BLL SNAP2162L SNAP2162GYL SNAP2162IL SNAP2162LAL SNAP2162RL SNAP2162WL
Isolated ground ^A , Specification grade, with LED.	Orange	SNAP2152IGL	SNAP2162IGL
Specification grade, Tamper-Resistant, with Power Indicating LED, Style Line decorator, flush, nylon face, modular receptacle which requires pigtailed connector below.	Black Blue Brown Gray Ivory Light Almond Red White	SNAP2152BKLTRA SNAP2152BLLTRA SNAP2152LTRA SNAP2152GYLTRA SNAP2152ILTRA SNAP2152LALTRA SNAP2152RLTRA SNAP2152WLTRA	SNAP2162BKLTRA SNAP2162BLLTRA SNAP2162LTRA SNAP2162GYLTRA SNAP2162ILTRA SNAP2162LALTRA SNAP2162RLTRA SNAP2162WLTRA
Isolated ground ^A , Specification grade, TR with LED.	Orange	SNAP2152IGLTRA	SNAP2162IGLTRA


Note: ^ASee section O additional information on isolated ground devices.
See page Tech-10 for Tamper-Resistant and LED Power Indicators descriptions.
See pages B-53 for accessories.
See section P for wallplates.




SNAP2162A




SNAP2162ITRA



SNAP2162GYL



SNAP2162RLTRA



SNAP5661LATR

SNAPConnect 250V Extra Heavy Duty Standard Single Receptacles

Description	Color	15A 250V	20A 250V
Specification grade, single modular receptacle Tamper-Resistant, smooth nylon face. Requires pigtailed connector on page B-14.	Black Brown Gray Ivory Light Almond White	SNAP5661BKTR SNAP5661BTR SNAP5661GYTR SNAP5661ITR SNAP5661LATR SNAP5661WTR	SNAP5461BKTR SNAP5461BTR SNAP5461GYTR SNAP5461ITR SNAP5461LATR SNAP5461WTR

Dimensions in Inches (mm)