

VTC-TNB8RFA3-2

Transcendent Series 8 MegaPixel [4K] Generation III Advanced A.I. Fixed IP Bullet Camera



VITEKCCTV.COM
(888) VITEK-70


TRANSCENDENT



KEY FEATURES

- 1/2.8" 8.0 Megapixel [4K] CMOS Image Sensor
- Up to 20fps live view @ 8 MegaPixel (3840x2160), 30fps @ 5/4/3MP/1080/720p/D1/CIF/480x240
- Available with 2.8mm Fixed Lens in Ivory or Charcoal:
VTC-TNB8RFA3-2 (Ivory w/ 2.8mm)
VTC-TNB8RFA3B-2 (Charcoal w/ 2.8mm)
- Supports Still Image Recording Function
- 2 Matrix IRs (up to 165' IR Range)
- True Wide Dynamic Range
- True Mechanical Day/Night function by ICR
- XD-DNR (3D & 2D Digital Noise Reduction)
- Gen. III Advanced Analytics: Abnormal Video, Face Detection, Regional Intrusion Detection, Regional Entrance / Exiting Detection, Line Crossing, Target Counting Detection
- 1 Channel Audio In*
- Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
- Remote Viewing via CMS, Internet Explorer, and iOS & Android Apps
- ONVIF Compliant
- MicroSD Card Slot for Local Recording (256GB)
- IP67 Weather Resistance
- Wall Mount Included and Optional Junction Box (VT-TJB08) Available [See Other Mounting Options Below]
- 12VDC & PoE (Power over Ethernet) Operation
- 3-Year Warranty

MOUNTS



VT-TJB08/B
Optional Junction Box
for Cable Management



VT-TPLMT
Universal Pole
Mount - Ivory,
reqs. VT-TJB08



VT-TCNMT
Universal Corner
Mount - Ivory, reqs.
VT-TJB08

RECORDERS



Pair with VITEK Transcendent Series DVRs, VT-TNR818PF, VT-TNR1646PF, and VT-TNR3216PF with Built-in PoE and Advanced Analytics including Face Detection.

SPECIFICATIONS

Image Sensor	1/2.8" 8.0 Megapixel [4K] CMOS Image Sensor
Image Size	8 MegaPixel (3840x2160)
Resolution	8MP(3840x2160), 6MP(3072x2048), 5MP(2592x1944), 4MP(2592x1520), 4MP(2560x1440), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), D1, CIF, 480x240
Min. Illumination	0.01 lux @ F1.2, AGC ON; 0 lux with IR, 0.02 lux@F1.6, AGC ON; 0 lux with IR
Lens	2.8mm Fixed Iris Lens
Day/Night	True Day/Night by ICR
IR LEDs / Distance	2 Matrix / 165'
Video Compression	Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
Audio Compression	G.711A / G.711U
Main-Stream	1~20fps: 8MP, 6MP, 1~30fps: 5MP, 4MP, 3MP, 1080P, 720P, D1, CIF, 480 x 240
Bit Rate	64Kbps ~ 12Mbps
Wide Dynamic Range (WDR)	120dB Super WDR
Digital Noise Reduction (DNR)	XD-DNR (2D-DNR & 3D-DNR)
Quality	VBR (Five Levels of Adjustment) / CBR (Adjustable)
Image Setting	Saturation, Brightness, Contrast, WDR, Noise reduction
Gen. III Advanced Analytics	Face Detection, Target Counting, Intrusion, Region Entrance / Exit, Line Crossing, Scene Change, Video Blur
Smart Alarm	Motion Detection, SD Card Error, SD Card Full
Region of Interest (ROI)	Each ROI to be Configured Separately
Network	RJ45
Audio	1 Ch. Audio In*
Local Storage	MicroSD Card Slot (Up to 256GB)
Remote Viewing	CMS / Web Browser / Mobile (iOS/Android)
Supported Browsers	Microsoft Internet Explorer
Connection Protocol	ONVIF
Ingress Protection	IP67
Power Input	12VDC / PoE
Power Consumpt. (12VDC)	350mA (LEDs Off) / 600mA (LEDs On)
Power Consumpt. (PoE)	< 9W
Working Environment	-22° ~ 140° / < 95% Humidity
Weight	22.93 oz. / 1.43 lbs. / 650g
Dimensions: L x W x H	8.68 x 3.15 x 2.78" (220.5 x 80.1 x 70.5mm)

*Please research local, state and federal laws regarding the implementation of audio surveillance.



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

An Eye On
Innovation