

# WLTC

Wet Location LED Emergency Exit Combination Light

## Emergency Power for Demanding Environments

The WLTC by Lithonia Lighting® is a high-performing wet location LED exit combination light that provides a minimum of 90-minutes of illumination upon the loss of AC power. It is designed with watertight, corrosion-resistant thermoplastic housing. The fixture is sealed and gasketed to protect the internal electronics from damp, wet, humid or dusty elements. This low-profile, unobtrusive unit with fully adjustable LED lamp heads allows for more accurate coverage and spacing requiring fewer products to get the job done.

### Features and Benefits

- Small, adjustable MR16 LED lamp heads for optimal spacing
- Magnetic test switch for easy manual initiation of monthly test
- Automatically performs monthly and annual testing with multi-status diagnostics functions



Learn more about the WLTC Emergency Exit Combination Light at [www.Lithonia.com](http://www.Lithonia.com)

## Wet Location Emergency Lights

	WLTC LED Emergency Combination Light	WLTE LED Emergency Exit Sign	WLTU LED Emergency Light	WLTU - MR Emergency Light
				
<b>Best Use</b>	Means of egress markings and illumination over doorways	Means of egress markings	Areas requiring emergency lighting	Areas requiring emergency lighting
<b>Mounting</b>	Top, back or end-mount	Top, back or end-mount	Wall-mount	Wall-mount
<b>Design</b>	Compact contemporary design	Low-profile contemporary design	Low-profile contemporary design	Compact and low-profile
<b>Housing/Construction</b>	Rugged, heavy-duty, polycarbonate clear housing lens	Rugged, polycarbonate housing and gasketed lens	Sealed and gasketed, polycarbonate housing and sealed exterior	High-impact, polycarbonate housing and gasketed lens
<b>Colors</b>	White and black	White, black and gray	Gray	Gray
<b>Letter/Signage</b>	Single face, red and green letters	Single or double face, red and green letters	N/A	N/A
<b>Ambient Temperature Range</b>	-4°F to 122°F (-20°C to 50°C)	-4°F to 122°F (-20°C to 50°C)	32°F to 122°F (0°C to 50°C)	68°F to 122°F (20°C to 50°C)
<b>Voltage</b>	Dual-voltage input capacity (120V/277V)	Dual-voltage input capacity (120V/277V)	Dual-voltage input capacity (120V/277V)	Dual-voltage input capacity (120V/277V)
<b>Optics</b>	Two adjustable lamp heads, 3.6W per head	< 5W Input Wattage	Two adjustable lamp heads, 1.9W per head	Two adjustable 7W wedge-based halogen MR16 style lamps
<b>Weight</b>	9.3 lbs (4.2 kg)	4.1 lbs (1.9 kg)	3.6 lbs (1.6 kg)	5.2 lbs (2.4 kg)
<b>Certifications/Ratings</b>	UL listed. Wet location listed. UL 924, NFPA 101 and NFPA-NEC	UL listed. Wet location listed. UL 924, NFPA 101 and NFPA-NEC	UL listed. Wet location listed. UL 924, NFPA 101, NFPA 70-NEC and OSHA illumination standards	UL listed. Wet location listed. UL 924, NFPA 101, NFPA 70-NEC and OSHA illumination standards
<b>Battery</b>	Sealed, maintenance-free, nickel-cadmium	AC only with optional maintenance-free, nickel-cadmium (EL Option)	Sealed, maintenance-free, nickel-cadmium	Sealed, maintenance-free, lead calcium
<b>Emergency Backup</b>	90-minutes minimum run time			
<b>Remote Capacity</b>	No	No	3.7W	No
<b>Warranty</b>	5-year limited warranty	5-year limited warranty	5-year limited warranty	3-year limited warranty
<b>Options</b>	Tamper-resistant screw hardware, self-diagnostics and cold weather	Tamper-resistant screw hardware, self-diagnostics	N/A	N/A
<b>Application</b>	Light industrial indoor applications that are subject to saturation with non-mechanically delivered water			

Visit [www.Lithonia.com](http://www.Lithonia.com) for more information.