

BX, Flex Connectors

90° - Squeeze Type with Insulated Throat- Zinc

Features


- Squeeze type with insulated throat

Applications

- Indoor use only
- In a dry location, use to connect flexible metallic conduit and AC and steel MC cable to a steel outlet box, or other metal enclosure
- 3/8" size fits 1/2" knockout
- Suitable for: 3/8" - 3/4" steel and aluminum armored cable, steel and aluminum interlocked metal clad cable, flexible cord, and 1" - 2" flexible metallic conduit

Standard Material

- Zinc die cast



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches			
						A	B (Min.-Max.)	C	Screws
100i	10341	3/8" 1/2" KO	50	500	45	1.74	.43 - .72	.37	2
101i	10351	1/2"	25	250	35	2.11	.64 - 1.03	.40	2
102i	10361	3/4"	10	100	20	2.40	.76 - 1.15	.40	2
103i	10371	1"	5	50	19	2.87	1.09 - 1.73	.54	2
104i	10381	1-1/4"	10	40	20	4	1.34 - 1.97	.64	2
105i	10391	1-1/2"	---	5	5	6	1.65 - 2.61	.75	2
106i	10401	2"	---	5	6	6	1.54 - 2.54	.74	2